

## DESCRIPTION

Quadrant enclosure with two fixed panels and two sliding doors.

## DIMENSIONS

- Standard height: 1950 mm.
- Special height: Up to 1950 mm.
- Standard width: From 770 to 900 mm, with 50 or 55 radius.
- Special width: Consult special dimensions, with total width up to 2000 mm.

## SERIE FEATURES



Expandable



6 mm

## AVAILABLE FINISHES



WHITE MAT



CHROME



RAL


## FEATURES

Entry calculation according to width:


- Width 770 - 800 x 770 - 800: 480 mm.
- Width 870 - 900 x 870 - 900: 530 mm.

- Tempered safety glass.
- Parts: Polyamide and Zamak.
- Profiles: First-fusion aluminium, alloy 6463 or 6063.
- Seals: UV-stable PVC with antifungal treatment.


Technical description (dimensions in mm)



PERFIL EXPANSOR  
D-2055




MARCO FIJO  
D-2056



GUÍA SUPERIOR E  
INFERIOR D-2053

## RODAMIENTO



## TESTING

The product is manufactured according to UNE-EN 14428: 2008, meeting all criteria within this standard, resulting in CE marking.

| APPLICABLE TESTS                         | EVALUATION METHODS                                                   | COMPLIANCE CRITERIA                                               | APTO |
|------------------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------|------|
| Cleaning suitability                     | Visual inspection (4.2)                                              | Free of sharp angles/edges, roughness or burrs (4.2)              | ✓    |
| Impact resistance/fracture properties    | 100 mm radius, minimum 40 particles (5.1, 5.2)                       | Tempered safety glass (4.3)                                       | ✓    |
| Corrosion resistance                     | 240 hours in salt spray(4.4.2)                                       | Corrosion resistant (4.4.2)                                       | ✓    |
| Resistance to chemicals and stains       | Reactants: acids, alkalis, alcohols, bleaches, coloring agents (5.3) | No deterioration or permanent discoloration (4.4.3)               | ✓    |
| Resistance to humidity and drying cycles | Submerge in water and dry for 50 cycles (5.4)                        | No cracks, microfissures or discoloration after 50 cycles (4.4.4) | ✓    |
| Endurance                                | 20.000 opening and closing cycles (5.5)                              | No functional deterioration (4.4.6)                               | ✓    |
| Stability                                | Impact resistance (5.6)                                              | Impact resistance without functional deterioration (4.4.6)        | ✓    |
| Water retention                          | Watertightness (5.7)                                                 | Retains water (4.4.7)                                             | ✓    |



DECLARACIÓN DE PRESTACIONES  
DOP: 02 MAMPARA CORREDERA  
UNE-EN 14428: 2008  
MAMPARAS DE DUCHA



ISO 14001: 2015  
CERTIFICADO DE  
GESTIÓN MEDIOAMBIENTAL



ISO 9001: 2015  
CERTIFICADO DE  
GESTIÓN DE CALIDAD

