

INSPEX HD VESA

HIGH-DEFINITION
DIGITAL MICROSCOPE





INSPEX HD VESA

HIGH-DEFINITION DIGITAL MICROSCOPE

Experience full HD image quality with no delay. The ideal solution for those wishing to digitise and simplify their inspection process.

Ergonomically designed, allowing for less operator fatigue and improved production efficiency.

Simple, fast, high-quality inspection. Ideal for repair, rework, assembly and quality control in any manufacturing industry.

FEATURES & BENEFITS

Instantly transform your production process with Inspex HD Vesa

Multiple Configurations

Inspex HD is available in several different configurations to meet your needs.

Short, long or flexible, the ultra-versatile Vesa can be tailored to meet your needs.

Superb Image Quality

Accurate and detailed inspection with superb HD image resolution, colour reproduction, contrast and resolution and integrated LED illumination.

Zero Video Latency

Real-time movement under Inspex HD, resulting in a more efficient inspection process.

View parts in real time with no video lag, allowing you to comfortably inspect, rework, modify or assemble anything.



FEATURES & BENEFITS

Instantly transform your production process with Inspex HD Vesa

Image Capture

Easy documentation and traceability for accurate quality control records. Store images directly to USB. Simply plug and go!

Working Distance

SLWD (Super Long Working Distance) objective lens for extra-large part viewing.

Wide Dynamic Range

View dark and bright areas simultaneously without saturation. Wide Dynamic Range uses overlapping multiple exposures depending on the saturation level of each pixel.

On Screen Dimensioning

Integrated, real time, on screen patented measuring grids and cursors provide a simple and effective way to measure without a PC.



Included System Components




	000
LENSES	OTHERS
+5 Lens	Memory Stick, HDMI Cable

Optional System Components

	O _i		+	
LENSES	LIGHTS	CONTROLLERS	STANDS & STAGE	ES .
+3 Lens AI 280-129	8-Point LED Ring Light AI 100-012	KP1 External Keypad Al 801-414 Required to activate dimensioning grids	XY Stage Al 100-010	Track Stand Vesa Flex Cam Al 100-028
+4 Lens AI 280-125	Polarizer for 8-Point LED Ring Light AI 100-000	Footswitch AI 801-415		Track Stand Vesa & Vesa Short Flex Cam Al 100-019
+5 Lens Al 280-123	Diffused LED Dome Light			Track Stand Vesa Short Al 100-020
+10 Lens AI 280-124	LED Fibre Optic Illuminator with Dual Gooseneck Al 100-033	OTHERS	XY Stage for Uplight	Uplight Track Stand Vesa & Vesa Short Flex Cam Al 100-023
Lens Polarizing Filter Al 280-145 Lens Protector Al 100-061	UV Ring Light AI 100-026 220V 254nm AI 100-005 220V 375nm AI 100-035 110V 254nm AI 100-034 110V 375nm	Ash PC Capture Al 100-052 24" Monitor Al 801-416	Oblique Tilting Stage Al 801-414 Height Adjustable Stage	78 100 023
		Hard Case Al 801-561 Soft Case	XY Stage Large	





Magnification

Lens (Dioptre) (mm)	2	3	4	5	10
Max Height (mm)	500	333	250	200	100
Min Height	405	280	205	170	85
Minimum Magnification*	1.1	1.3	2	2.5	4
Maximum Magnification* Optical/ Digital	29/57	36/71	50/98	62/122	121/237
Field of view at minimum mag. (mm)	X: 595	X: 400	X: 280	X: 231	X: 60
	Y: 334	Y: 225	Y: 164	Y: 136	Y: 50
Field of view at maximum mag. (mm)	X: 20/10	X: 14/7	X: 10/5	X: 8/4	X: 5/2
	Y: 11/5.5	Y: 8/4	Y: 6/3	Y: 5/2	Y: 3/1
Maximum depth of field	176	120	106	78	57
Minimum depth of field	5	4	1	.50	.20

Technical Specifications

	Vesa		
Zoom Range (with supplied Lens)	5D Lens – 2.5x - 122x		
Camera Resolution	HD 1080p, 1920 x 1080 at 50/60 Hz		
Monitor Connections	HDMI / DVI		
Monitor Requirements	HD Ready / Full HD (Recommended)		
Power	8 Watts		
Dimensions	370mm x 120mm x 140mm		
Weight	1.2kg		
Operating Temperature	Storage -10°C to +60°C Operating +5°C to +40°C		
Image capture	USB 2.0 highspeed	1	



ASH HQ - Ireland B5, M7 Business Park, Naas, Co. Kildare W91 P684 +353 (0) 45 88 22 12

ASH UK
Covert Farm, Long Lane,
Easte Haddon,
Northamptonshire
NN6 8DU
+44 (0) 7592 523 767









sales@ashvision.com www.ashvision.com



