


TITLE		<b>NOTE:</b> Purewater sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.	DESCRIPTION:  PW.3x2x1.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap.	DATE	VERSION	NOTES	TANK SPECIFICATION :				
PW.3x2x1.TIF.AB				24/01/2023	A	FIRST ISSUE					
DRAWN BY	N.Amechi			DATE	30/01/2023					INTERNAL DIMENSIONS	3150 x 2150 x 1150mm
CUSTOMER	CUSTOMER									EXTERNAL DIMENSIONS	3224 x 2224 x 1710mm
										NOM. CAPACITY	7,788 Litres
										INSULATION THICKNESS	38mm
										MATERIAL	Hot press moulded GRP
		ALL DIMENSIONS+/- 5mm UNLESS OTHERWISE STATED	A4	ALL DIMENSIONS IN MM - DO NOT SCALE					SCALE:1:40	SHEET 1 OF 1	