

NOTES:
DO NOT SCALE FROM DRAWING.
DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM
COMPONENTS ARE INTENDED TO BE
'INDICATIVE' ONLY.

NOTE A: INCORPORATE A MINIMUM 38mm WIDE, UNOBSTRUCTED, VENTILATED AND DRAINED CAVITY ['AIR GAP'] BETWEEN THE REAR OF THE BARRACUDA RAILS AND THE FRONT FACE OF THE 'BACKING WALL' OR FRONT FACE OF ANY EXTERNAL INSULATION.

NOTE B: INCORPORATE [AS APPROPRIATE] VAPOUR CONTROL AND/OR WATERPROOFING MEMBRANES.MEMBRANES MUST BE CONTINUOUS AND MECHANICALLY AND OR ADHESIVELY FIXED [AS APPROPRIATE]. MEMBRANES MUST BE COMPLETELY SEALED AND SEALED AT ALL JOINTS AND FIXING PENETRATIONS.

NOTE C: INCORPORATE 'THERMAL BREAKS' TO REDUCE THERMAL TRANSMITTANCE AT EACH BRACKET LOCATION.

01	FIRST ISSUE	JSC	26/06/2025
REV:	REVISION DETAIL:	CHKD:	DATE:

Barracuda

BRICK SLIP SUPPORT SYSTEM

DESIGN PRINCIPLES

TITLE:
CAVITY VENTILATION,
DRAINAGE AND THERMAL
TRANSMITTANCE

DATE:
26/06/2025



SCALE:
1:1

PLOT SIZE:
A3

DRAWING NUMBER:
DP-B-001

REVISION:
01

