



TITLE	
PW.5x2x2.TIF.AG	
DRAWN BY	J. Ellison
DATE	30/01/2023
CUSTOMER	CUSTOMER

<b>NOTE:</b> Purewater sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4

<b>DESCRIPTION:</b>  PW.5x2x2.TIF Sectional cold water storage tank c/w access manway to provide an AG Air gap	
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
23/01/2023	A	FIRST ISSUE

<b>TANK SPECIFICATION :</b>		
INTERNAL DIMENSIONS	5150 x 2150 x 2150mm	
EXTERNAL DIMENSIONS	5224 x 2223 x 2351mm	
NOM. CAPACITY	23,805 Litres	
INSULATION THICKNESS	38mm	
MATERIAL	Hot press moulded GRP	

SCALE:1:55	SHEET 1 OF 1