



Longwrap
Technical Data Sheet

DESCRIPTION	Longwrap Petrolatum Paste is a VOC Free, cold applied, wax based primer. It completely wets out the substrate surface and displaces any moisture prior to the application of all grades of Longwrap Petrolatum tape and LD Mastic. Longwrap Petrolatum Paste is also suitable for use with Longwrap Marine Tape. The Paste can be applied underwater and will displace water and fill any voids prior to the application of the Marine Tape.
SUBSTRATE COMPATIBILITY	Steel, Stainless Steel, Ductile Iron, Other Metals, FBE, PE, PP, Concrete
RECOMMENDED USE	Ideal for protecting structures such as fittings, flanges, valves, mechanical couplings, vault piping and other complex piping and metal structures.
SURFACE PREPARATION	SSPC SP-2 Hand Tool Cleaning, SSPC SP-3 Power Tool Cleaning or SSPC SP-6/ NACE No. 3 Commercial Blast Cleaning
REFERENCE	Petrolatum Paste and the Longwrap tapes together meet all of the performance criteria listed in the most recent revisions of: NACE RP0375 (Cold-Applied Wax-Tape Coating System) ANSI/AWWA C217
SAFETY	Refer to Material Safety Data Sheet: MSDS-Petrolatum-Paste
APPLICATION	Refer to Application Guidelines: AG-COLD-APPLIED-PET-LONGWRAP

TYPICAL DATA

Property	Metric	US Customary	Test Method
Color	Brown	Brown	
VOC Content	0 g/l	0 lb/gal	
Specific Gravity	1.1	1.1	ASTM D1475
Service Temperature Range	-29° C to 121° C	-20° F to 250° F	

ORDERING INFORMATION

Packaging	2.5 kg pail
------------------	-------------

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

Chase Protective Coatings Ltd
 Harbour Road,
 Rye, East Sussex, TN31 7TE, UK
 Phone: +44(0)1797.223561
 Fax: +44(0)1797.224530
 www.chasecorp.com
 A BS EN ISO 9001:2008
 REGISTERED COMPANY

Chase Corporation
 295 University Avenue
 Westwood, MA 02090
 Phone: 800-323-4182
 Fax: 781-332-0701
 An ISO 9001:2008
 REGISTERED COMPANY