

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Serviwrap Primer AB
Registration number	-
Synonyms	None.
Issue date	10-03-2018
Version number	02
Revision date	10-24-2018
Supersedes date	10-03-2018

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Primer for Corrosion Protection and Waterproofing Products
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	Chase Protective Coatings Ltd	
Address	A CHASE CORPORATION COMPANY Harbour Road Rye, East Sussex, TN31 7TE UK	
Division		
Telephone	General Assistance	+44 (0)1797 223561
e-mail	info@chaseprotectivecoatings.com	
Contact person	Not available.	

1.4. Emergency telephone number	Emergency Phone	44 (0)1797 223561
	(M-Th 9:00-5:30; F 9:00-3:00)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapor.
-------------------	------------	------------------------------------

Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.

Hazard summary	May be ignited by heat, sparks or flames. Harmful if inhaled. Harmful in contact with skin. Causes skin irritation. Occupational exposure to the substance or mixture may cause adverse health effects.
-----------------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended**Contains:** Bitumen, XYLENES**Hazard pictograms****Signal word** Warning**Hazard statements**

H226 Repeated exposure may cause skin dryness or cracking.
 Flammable liquid and vapor.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H332 Harmful if inhaled.

Precautionary statements**Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing vapors.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

55% of the mixture consists of component(s) of unknown acute oral toxicity. 55% of the mixture consists of component(s) of unknown acute dermal toxicity. 55% of the mixture consists of component(s) of unknown acute inhalation toxicity. 100% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 100, 55% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards

Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Bitumen	50 - < 60	64742-93-4 265-196-4	01-2119498270-36	-	
Classification:	-				
XYLENES	40 - < 50	1330-20-7 215-535-7	-	601-022-00-9	#
Classification:	Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, Acute Tox. 4;H332				C

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).
 M: M-factor
 PBT: persistent, bioaccumulative and toxic substance.
 vPvB: very persistent and very bioaccumulative substance.
 All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
4.1. Description of first aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effects, both acute and delayed	Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Flammable liquid and vapor.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
XYLENES (CAS 1330-20-7)	MAK	221 mg/m ³
		50 ppm
	STEL	442 mg/m ³
		100 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm
	TWA	221 mg/m ³
		50 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm
	TWA	221 mg/m ³
		50 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
XYLENES (CAS 1330-20-7)	MAC	221 mg/m ³
		50 ppm
	STEL	442 mg/m ³
		100 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
XYLENES (CAS 1330-20-7)	Ceiling	400 mg/m ³
	TWA	200 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
XYLENES (CAS 1330-20-7)	TLV	109 mg/m ³
		25 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	450 mg/m ³

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
		100 ppm
	TWA	200 mg/m ³
		50 ppm

Finland. Workplace Exposure Limits Components

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	440 mg/m ³
		100 ppm
	TWA	220 mg/m ³
		50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
XYLENES (CAS 1330-20-7)	VLE	442 mg/m ³
Regulatory status:	Regulatory binding (VRC)	
		100 ppm
Regulatory status:	Regulatory binding (VRC)	
	VME	221 mg/m ³
Regulatory status:	Regulatory binding (VRC)	
		50 ppm
Regulatory status:	Regulatory binding (VRC)	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
XYLENES (CAS 1330-20-7)	TWA	440 mg/m ³
		100 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
XYLENES (CAS 1330-20-7)	AGW	440 mg/m ³
		100 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	650 mg/m ³
		150 ppm
	TWA	435 mg/m ³
		100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
	TWA	221 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm
	TWA	109 mg/m ³
		25 ppm

Ireland. Occupational Exposure Limits Components

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm

Ireland. Occupational Exposure Limits Components

Type	Value
TWA	221 mg/m ³ 50 ppm

Italy. Occupational Exposure Limits Components

Type	Value
STEL	442 mg/m ³ 100 ppm
TWA	221 mg/m ³ 50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components

Type	Value
STEL	442 mg/m ³ 100 ppm
TWA	221 mg/m ³ 50 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components

Type	Value
STEL	450 mg/m ³ 100 ppm
TWA	200 mg/m ³ 50 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A Components

Type	Value
STEL	442 mg/m ³ 100 ppm
TWA	221 mg/m ³ 50 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V) Components

Type	Value
STEL	442 mg/m ³ 100 ppm
TWA	221 mg/m ³ 50 ppm

Netherlands. OELs (binding) Components

Type	Value
STEL	442 mg/m ³
TWA	210 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace Components

Type	Value
TLV	108 mg/m ³ 25 ppm

Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components

Type	Value
TWA	100 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266) Components

Type	Value
STEL	442 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
		100 ppm
	TWA	221 mg/m3
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
XYLENES (CAS 1330-20-7)	TWA	221 mg/m3
		50 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
XYLENES (CAS 1330-20-7)	Ceiling	442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	870 mg/m3
		200 ppm
	TWA	435 mg/m3
		100 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	441 mg/m3
		100 ppm
	TWA	220 mg/m3
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
XYLENES (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm
	TWA	221 mg/m ³
		50 ppm

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1,5 g/g	Methylhippuric acids	Creatinine in blood	*
	1,5 mg/l	xylene	Blood	*
	0,88 mol/mol	Methylhippuric acids	Creatinine in blood	*
	14,13 umol/l	xylene	Blood	*

* - For sampling details, please see the source document.

Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1500 mg/g	Acides méthylhippuriques	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-)säure (alle Isomere)	Urine	*
	1,5 mg/l	Xylol	Blood	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1500 mg/g	methyl hippuric acids	Creatinine in urine	*
	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time
	1,5 mg/l	xylene	Blood	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	1,5 g/g	Methyl-Hippursäure	Creatinine in urine	*
	1,5 mg/l	Xylol	Blood	*

* - For sampling details, please see the source document.

UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen	Sampling Time
XYLENES (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

EU Exposure Limit Values: Skin designation

XYLENES (CAS 1330-20-7) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

XYLENES (CAS 1330-20-7) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Gloves of nitrile rubber, PVA or Viton are recommended.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. A "Class A" filter per EN 14387 is recommended.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Black.

Odor Aromatic

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 278,6 - 284 °F (137 - 140 °C)

Flash point > 75,2 °F (> 24,0 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0,8 %

Explosive limit - upper (%) 6,7 %

Vapor pressure 10,65 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble in water

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature > 910,4 °F (> 488 °C)

Decomposition temperature Not available.

Viscosity > 50 mPa·s

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

9.2. Other information

Density 0,96 g/cm³

Percent volatile 45 % estimated

Specific gravity 0,92 - 0,96

VOC < 592 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong acids. Strong oxidizing agents. Halogens.

10.6. Hazardous decomposition products No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Harmful in contact with skin. Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
XYLENES (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 - 8600 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization	Due to partial or complete lack of data the classification is not possible.	
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.	
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.	
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)		
Not listed.		
IARC Monographs. Overall Evaluation of Carcinogenicity		
Bitumen (CAS 64742-93-4)	2A Probably carcinogenic to humans.	
XYLENES (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.	
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.	
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.	
Mixture versus substance information	No information available.	
Other information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity Due to partial or complete lack of data the classification for hazardous to the aquatic environment, is not possible. Due to partial or complete lack of data the classification for hazardous to the aquatic environment, acute hazard, is not possible.

Product	Species	Test Results
Servivrap Primer AB		
Aquatic		
Fish	LC50 Fish	102,4943 mg/l, 96 hours estimated
Components		
XYLENES (CAS 1330-20-7)		
Aquatic		
Fish	LC50 Bluegill (Lepomis macrochirus)	7,711 - 9,591 mg/l, 96 hours
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
12.3. Bioaccumulative potential		
Partition coefficient n-octanol/water (log Kow)		
XYLENES	3,12 - 3,2	
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	No data available.	
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture. Not available.	
12.6. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

12.7. Additional information

Estonia Dangerous substances in groundwater Data

XYLENES (CAS 1330-20-7)

Pesticides (total) 0,5 UG/L

Pesticides (total) 5 UG/L

Estonia Dangerous substances in soil Data

XYLENES (CAS 1330-20-7)

Synthetic pesticides (total of active substances) 0,5 MG/KG

Synthetic pesticides (total of active substances) 20 MG/KG

Synthetic pesticides (total of active substances) 5 MG/KG

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint Related Material (Xylene (mixture of isomers))
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint Related Material (Xylene (mixture of isomers))
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint Related Material (Xylene (mixture of isomers))
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1263
------------------------	--------

14.2. UN proper shipping name	Paint Related Material (Xylene (mixture of isomers))
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint Related Material (Xylene (mixture of isomers))
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-E, S-E
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code	Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
XYLENES (CAS 1330-20-7)
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

XYLENES (CAS 1330-20-7)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapor.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.

Revision information

Product and Company Identification: Product and Company Identification
SECTION 2: Hazards identification: Hazard summary
SECTION 2: Hazards identification: Hazard statements
SECTION 2: Hazards identification: Specific hazards
Composition / Information on Ingredients: Ingredient Classification
SECTION 3: Composition/information on ingredients: Composition comments
SECTION 3: Composition/information on ingredients: Component information
SECTION 6: Accidental release measures: 6.3. Methods and material for containment and cleaning up
SECTION 8: Exposure controls/personal protection: - Hand protection
SECTION 8: Exposure controls/personal protection: Respiratory protection
Physical & Chemical Properties: Multiple Properties
SECTION 9: Physical and chemical properties: Odor
SECTION 11: Toxicological information: Acute toxicity
SECTION 11: Toxicological information: Inhalation

Training information

Follow training instructions when handling this material.

Issued by

Dan Libby

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.