



## Product Data Sheet

### Description

WRAPKOTE LS911 Leak Stopper Strap is the all-in-one wrap around instant leak stopper, designed for all pipe systems. This innovative product requires no special tools and is capable of sealing leaks even under pressure. WRAPKOTE LS911 Leak Stopper Strap is a stand-alone system. It can be used over and over again, reducing maintenance downtime.

WRAPKOTE LS911 Leak Stopper Strap is made from high temperature EPDM rubber (-40°C - +120°C (-40°F to 248°F)) and has a wide chemical resistance.

WRAPKOTE LS911 Leak Stopper Strap is a must for all plumbers, maintenance and heating engineers.

### Properties

Max heat resistance -40°C to 120°C

Max service pressure 10 bar (150 psi)

**Always consult the Parker James Protective Coatings Ltd technical dept for more information.**

### Colours

Black

### Pack Size

30mm x 0.70m

50mm x 0.90m

### Application

Ensure that the surface of the pipe around leak is free from grease and loose debris before you start. Hold rubber strap over leaking area. Always stretch the rubber and wrap around pipe maintaining tension, when fully wrapped lock off with Velcro.

### Storage and Health and Safety

Store in dry conditions, out of direct sunlight, at temperatures between 10°C and 25°C. This product has a minimum shelf life of 60 months when stored in original, unopened containers in accordance with manufacturer's instructions.

### Other Information

The information contained in this DATA SHEET, as well as our advice, both written as verbal or provided through testing, are based on our experience, and they do not constitute any product guarantee for the installer, who must consider them as simple information. We recommend to study deeply all information provided before proceeding to the use or application of any of our products, and strongly advise to conduct tests "on-site" in order to determine their convenience for a specific project. Our recommendations do not exempt of the obligation of installers to deeply study the right application method for these systems before use, as well as to conduct as many preliminary tests as possible should any doubt arise. The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. In consequence, the installer will be the only responsible of any damage derived from the partial or total in-observation of our indications, and in general, of the inappropriate use or application of these materials.

**Parker James Protective Coatings Limited | 4 Aldridge Depot  
WS9 8SR | 01922 457664 | sales@parkerjames.co.uk**