

HPR-810-SP BASE

Page: 1

Compilation date: 21/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HPR-810-SP BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Parker James Protective Coatings Ltd

Unit 4 Aldridge Depot, Brickyard Road, Aldridge, Walsall West Midlands, WS9 8SR United Kingdom

Tel: +44 (0) 1922 457664

Email: sales@parkerjames.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1423 325073

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43; N: R51/53

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -:

EUH205

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic

organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements:

Hazard statements: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental

[cont...]

HPR-810-SP BASE

Page: 2





Precautionary statements: P102: Keep out of reach of children.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release to the environment.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Irritant.

Dangerous for the environment.





Risk phrases: R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin. S29: Do not empty into drains. S37: Wear suitable gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains epoxy constituents. See information supplied by the manufacturer.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent

HPR-810-SP BASE

	1-1	40	•	
г	ay	J۳		

500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%
BISPHENOL F	TYPE EPOXY RI	ESIN		
500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
OXIRANE, MON	NO[(C12-14ALKY	LOXY)METHYL] DERIVATIVES		
271-846-8	68609-97-2	Xi: R38; Sens.: R43	Skin Irrit. 2: H315; Skin Sens. 1: H317	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

HPR-810-SP BASE

Page: 4

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct

sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.

Skin protection: Impermeable protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

HPR-810-SP BASE

Page: 5

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >150

Relative density: 1.15g/cc

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Amines. Alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>2000	mg/kg
ORAL	RBT	LD50	>2000	mg/kg

HPR-810-SP BASE

Page: 6

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES

ORL	RAT	LD50	17100	mg/kg	

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	2	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

HPR-810-SP BASE

Page: 7

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Mixed material, once fully cured, can be disposed as solid waste.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

HPR-810-SP BASE

Page: 8

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.



HPR-810-SP ACTIVATOR

Page: 1

Compilation date: 27/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HPR-810-SP ACTIVATOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:

Parker James Protective Coatings Ltd

Unit 4 Aldridge Depot, Brickyard Road, Aldridge, Walsall West Midlands, WS9 8SR United Kingdom

Tel: +44 (0) 1922 457664 **Email:** <u>sales@parkerjames.co.uk</u>

1.4. Emergency telephone number

Emergency tel: +44 (0) 1423 325073

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Corr. 1A: H314; Skin Sens. 1A: H317

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark





[cont...]

Precautionary statements: P102: Keep out of reach of children.

P273: Avoid release to the environment.

P260: Do not breathe vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.S37: Wear suitable gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302	10-30%

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

217-168-8	1761-71-3	-	Skin Corr. 1A: H314; Aquatic Chronic	10-30%
			2: H411	

TRIMETHYLHEXANE-1,6-DIAMINE

	•			
247-063-2	25513-64-8	C: R34; Xn: R22; Sens.: R43	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H312	1-10%
P-TOLUENE	SULPHONIC ACI	D MONOHYDRATE		
203-180-0	6192-52-5	Xi: R36/37/38	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10

minutes. If unconscious, check for breathing and apply artificial respiration if necessary.

If unconscious and breathing is OK, place in the recovery position. Transfer to hospital

as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and

away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the

escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage

container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown
Odour: Ammoniacal

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >100

Autoflammability°C: 380 Relative density: 1.0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

DERMAL	RBT	LD50	2110	mg/kg
ORAL	RAT	LD50	625	mg/kg

TRIMETHYLHEXANE-1,6-DIAMINE

DERMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	910	mg/kg

P-TOLUENE SULPHONIC ACID MONOHYDRATE

ORAL RAT LD50	2480 mg/kg
---------------	------------

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

Daphnia magna	48H EC50	6.84	mg/l

TRIMETHYLHEXANE-1,6-DIAMINE

FISH	48H EC50	174	ma/l
1 1011	48H EC50	117	1119/1

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.

(TRIMETHYLHEXANE-1,6-DIAMINE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

R20/22: Harmful by inhalation and if swallowed.

R22: Harmful if swallowed.

R34: Causes burns.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.