


TITLE		NOTE:		DESCRIPTION:	DATE	VERSION	NOTES	TANK SPECIFICATION :			
PW501-UN		All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.			07/01/2022	A	FIRST ISSUE	INTERNAL DIMENSIONS	1000 x 500 x 1000mm		
DRAWN BY J. Ellison		DATE 07/01/2022		PW501-UN One piece cold water storage tank suitable for AG/AF Air gap				EXTERNAL DIMENSIONS	1180 x 680 x 1017mm	SCALE:1:20	
								NOM. CAPACITY	500 Litres		
								DRY WEIGHT	42 KG		
								INSULATION THICKNESS	NONE		
								WRAS CERT. NUMBER	131006		
CUSTOMER		ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4	ALL DIMENSIONS IN MM - DO NOT SCALE			MATERIAL	GRP	SHEET 1 OF 1	