



TITLE		PW1590-UN	
DRAWN BY	J. Ellison	DATE	07/01/2022
CUSTOMER	CUSTOMER		

NOTE	
All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4

DESCRIPTION:	
PW1590-UN One piece cold water storage tank suitable for AG/AF Air gap	
ALL DIMENSIONS IN MM	DO NOT SCALE

DATE	VERSION	NOTES
07/01/2022	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1524 x 1143 x 915mm
EXTERNAL DIMENSIONS	1700 x 1310 x 1008mm
NOM. CAPACITY	1590 Litres
DRY WEIGHT	115 KG
INSULATION THICKNESS	NONE
WRAS CERT. NUMBER	131006
MATERIAL	GRP

purewater storage ltd	
SCALE:1:30	SHEET 1 OF 1