


TITLE		NOTE: All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.		DESCRIPTION:		DATE 10/01/2022		VERSION A		NOTES FIRST ISSUE		TANK SPECIFICATION :							
PW2272-UN				PW2272-UN One piece cold water storage tank suitable for AG/AF Air gap								INTERNAL DIMENSIONS		1828 x 1220 x 1016mm					
												EXTERNAL DIMENSIONS		2020 x 1410 x 1109mm					
												NOM. CAPACITY		2272 Litres					
												DRY WEIGHT		150 KG					
												INSULATION THICKNESS		NONE					
DRAWN BY J. Ellison		DATE 10/01/2022										WRAS CERT. NUMBER		131006		SCALE:1:30		SHEET 1 OF 1	
CUSTOMER CUSTOMER				ALL DIMENSIONS+/- 5mm UNLESS OTHERWISE STATED		A4		ALL DIMENSIONS IN MM		DO NOT SCALE		MATERIAL		GRP					