


TITLE		NOTE: All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.		DESCRIPTION:		DATE 10/01/2022		VERSION A		NOTES FIRST ISSUE		TANK SPECIFICATION :							
DRAWN BY J. Ellison				DATE 10/01/2022				PW3185-UN One piece cold water storage tank suitable for AG/AF Air gap				INTERNAL DIMENSIONS		2440 x 1220 x 1070mm					
												EXTERNAL DIMENSIONS		2610 x 1410 x 1163mm					
												NOM. CAPACITY		3185 Litres					
												DRY WEIGHT		175 KG					
												INSULATION THICKNESS		NONE					
CUSTOMER CUSTOMER				ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4		ALL DIMENSIONS IN MM		DO NOT SCALE		WRAS CERT. NUMBER		131006		SCALE:1:35		SHEET 1 OF 1	
										MATERIAL		GRP							