


TITLE		NOTE:		DESCRIPTION:		DATE		VERSION		NOTES		TANK SPECIFICATION :			
PW3750-UN		All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.		PW3750-UN One piece cold water storage tank suitable for AG/AF Air gap		10/01/2022		A		FIRST ISSUE		INTERNAL DIMENSIONS 2500 x 1500 x 1000mm			
DRAWN BY J. Ellison		DATE 10/01/2022										EXTERNAL DIMENSIONS 2694 x 1694 x 1093mm			
CUSTOMER		CUSTOMER		ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4		ALL DIMENSIONS IN MM		DO NOT SCALE		NOM. CAPACITY 3750 Litres			
												DRY WEIGHT 210 KG			
												INSULATION THICKNESS NONE			
												WRAS CERT. NUMBER 131006		SCALE:1:35	
												MATERIAL GRP		SHEET 1 OF 1	