


TITLE PW2501-UN			<div>NOTE: All Purewater tanks must be fully supported on a flat level &amp; continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.</div>			<div>DESCRIPTION: PW2501-UN One piece cold water storage tank suitable for AG/AF Air gap</div>			<div>DATE 20/12/2023</div>			<div>VERSION A</div>			<div>NOTES FIRST ISSUE</div>			TANK SPECIFICATION :						<div></div>				
DRAWN BY J. Ellison		DATE 20/12/2023																			INTERNAL DIMENSIONS 2000 x 1000 x 1250mm							
CUSTOMER CUSTOMER									ALL DIMENSIONS+/- 5mm UNLESS OTHERWISE STATED			A4			ALL DIMENSIONS IN MM - DO NOT SCALE											EXTERNAL DIMENSIONS 2182 x 1182 x 1343mm		
																										NOM. CAPACITY 2500 Litres		
																		DRY WEIGHT 178KG										
																		INSULATION THICKNESS NONE										
																		WRAS CERT. NUMBER 131006										
																		MATERIAL GRP										
																		SCALE: 1:25			SHEET 1 OF 1							