

Grp One Piece Cold water storage tanks

A comprehensive range of one piece cold water storage tanks manufactured from WRAS approved Grp materials.

Fully encapsulated insulation to sides and lid.

Close fitting and sealed lid which is removable for maintenance.

Tanks storing over 1000 litres nominal have an access man-way with removable lid providing a 520 x 520mm opening, allowing access for maintenance and inspection.

Applications

Suitable for all cold water applications including:

- Potable and Non potable water storage.
- Process water (including process cooling) applications -15° to +30°c

Provides mains water protection for fluid category 1,2,3 & 4 with standard lid arrangement & fluid category 5 when back flow protection is required.

Approvals & Certification

Full WRAS approval

Manufactured to BS EN 13280:2001


Quality System manufactured in accordance with ISO 9001: 2000

Specification - General

Manufactured from highest quality Grp materials.
CFC free PU foam insulation is completely encapsulated within the Grp laminate.

Structural support where required is provided by rolled hollow section steel, braced with welded corner angles, which is then completely encapsulated within the Grp laminate.

The outer surface of the tank is coated with polyester gel coat to ensure tank suitability for external positioning in most extremes of weather as standard.



Optional items for this product range include:

- Raised float valve housings.
- Equilibrium and BS1212 float valves.
- Aylesbury "Keraflo" delayed action float valves.
- Screened overflows & warning pipes.
- Flanged tank connectors.
- Float operated switches to suit level control.
- Temperature sensors.
- Level gauges.
- Drip trays.
- Encapsulated ply base.
- Steel support frames.
- Fitted with internal divisions or weir plates.

and much more....

For details of optional items, please refer to our website: www.purewaterstorage.co.uk

Grp One Piece Standard tank range



Please note...


All tanks available with AG,AF or AB air gaps please ask for further information.

All of these tanks are available as two piece units for applications where access is restricted. Un-insulated tanks are also available for non-potable applications.

We can also manufacture bespoke tanks to your specific size and configuration requirements.

For details, please refer to the relevant information sheets or visit our website:

www.purewaterstorage.co.uk



Imperial configuration tanks	Product	Nominal Capacity	Internal Dimensions	External Dimensions
	PW90.INS	90 litres	610 x 305 x 510mm high	775 x 478 x 522mm high
	PW160.INS	160 litres	760 x 460 x 460mm high	950 x 655 x 499mm high
	PW225.INS	225 litres	610 x 610 x 610mm high	795 x 795 x 650mm high
	PW338.INS	338 litres	610 x 610 x 910mm high	795 x 795 x 950mm high
	PW340.INS	340 litres	915 x 610 x 610mm high	1080 x 775 x 622mm high
	PW454.INS	454 litres	1067 x 610 x 710mm high	1245 x 795 x 727mm high
	PW570.INS	570 litres	990 x 760 x 760mm high	1150 x 925 x 799mm high
	PW650.INS	650 litres	1067 x 610 x 1000mm high	1245 x 795 x 1017mm high
	PW680.INS	680 litres	1220 x 915 x 610mm high	1395 x 1087 x 649mm high
	PW712.INS	712 litres	1090 x 860 x 760mm high	1240 x 1010 x 796mm high
	PW909.INS	909 litres	1168 x 890 x 890mm high	1330 x 1050 x 929mm high
	PW1135.INS	1135 litres	1524 x 915 x 812mm high	1680 x 1080 x 905mm high
	PW1364.INS	1364 litres	1370 x 1092 x 915mm high	1570 x 1290 x 1008mm high
	PW1590.INS	1590 litres	1524 x 1143 x 915mm high	1700 x 1310 x 1008mm high
Metric configuration tanks	Product	Nominal Capacity	Internal Dimensions	External Dimensions
	PW125.INS	125 litres	500 x 500 x 500mm high	675 x 675 x 518mm high
	PW187.INS	187 litres	500 x 500 x 750mm high	675 x 675 x 765mm high
	PW250.INS	250 litres	1000 x 500 x 500mm high	1160 x 660 x 517mm high
	PW251.INS	250 litres	500 x 500 x 1000mm high	675 x 675 x 1018mm high
	PW305.INS	305 litres	500 x 500 x 1220mm high	675 x 675 x 1237mm high
	PW375.INS	375 litres	500 x 500 x 1500mm high	675 x 675 x 1517mm high
	PW500.INS	500 litres	1000 x 1000 x 500mm high	1172 x 1172 x 539mm high
	PW501.INS	500 litres	1000 x 500 x 1000mm high	1160 x 660 x 1017mm high
	PW601.INS	600 litres	1000 x 500 x 1200mm high	1160 x 660 x 1217mm high
	PW750.INS	750 litres	1500 x 1000 x 500mm high	1702 x 1202 x 536mm high
	PW751.INS	750 litres	1000 x 1000 x 750mm high	1172 x 1172 x 789mm high
	PW825.INS	825 litres	1500 x 500 x 1100mm high	1665 x 665 x 1140mm high
	PW1000.INS	1000 litres	1000 x 1000 x 1000mm high	1160 x 1160 x 1093mm high
	PW1050.INS	1050 litres	1500 x 500 x 1400mm high	1665 x 665 x 1477mm high
	PW1125.INS	1125 litres	1500 x 500 x 1500mm high	1665 x 665 x 1577mm high
	PW1220.INS	1220 litres	1000 x 1000 x 1220mm high	1160 x 1160 x 1313mm high
	PW1500.INS	1500 litres	1500 x 1000 x 1000mm high	1702 x 1202 x 1093mm high
	PW1501.INS	1500 litres	1000 x 1000 x 1500mm high	1160 x 1160 x 1593mm high
	PW2000.INS	2000 litres	2000 x 1000 x 1000mm high	2180 x 1180 x 1093mm high
	PW2001.INS	2000 litres	1000 x 1000 x 2000mm high	1180 x 1180 x 2093mm high
	PW2250.INS	2250 litres	1500 x 1000 x 1500mm high	1702 x 1202 x 1593mm high
	PW2501.INS	2500 litres	2000 x 1000 x 1250mm high	2180 x 1180 x 1343mm high
	PW3000.INS	3000 litres	3000 x 1000 x 1000mm high	3202 x 1202 x 1093mm high
	PW3001.INS	3000 litres	2000 x 1000 x 1500mm high	2180 x 1180 x 1593mm high
	PW3750.INS	3750 litres	2500 x 1500 x 1000mm high	2694 x 1694 x 1093mm high
	PW4000.INS	4000 litres	2000 x 2000 x 1000mm high	2192 x 2192 x 1093mm high
	PW4001.INS	4000 litres	2000 x 1000 x 2000mm high	2180 x 1180 x 2093mm high
	PW4500.INS	4500 litres	2500 x 1500 x 1200mm high	2694 x 1694 x 1293mm high
	PW5000.INS	5000 litres	2500 x 2000 x 1000mm high	2692 x 2192 x 1093mm high
	PW5625.INS	5625 litres	2500 x 1500 x 1500mm high	2694 x 1694 x 1593mm high
	PW6000.INS	6000 litres	3000 x 2000 x 1000mm high	3192 x 2192 x 1093mm high
	PW6001.INS	6000 litres	2000 x 2000 x 1500mm high	2192 x 2192 x 1593mm high
	PW7500.INS	7500 litres	2500 x 2000 x 1500mm high	2692 x 2192 x 1593mm high
	PW9000.INS	9000 litres	3000 x 2000 x 1500mm high	3192 x 2192 x 1593mm high
	PW12000.INS	12000 litres	3000 x 2000 x 2000mm high	3192 x 2192 x 2093mm high
Raised float valve housing	Product	To suit valve type		Addition to overall tank height
	FVH4	Up to 54mm aylesbury & Equilibrium		+340mm
	FVH5	65mm + & multiple valves		+450mm or higher depending on size of valve
	FVH6	Up to 28mm Equilibrium		+310mm