

GPS Small Antenna Module

- GPS Active Antenna
- 17dB Gain
- High Sensitivity
- Low current consumption
- Additional MMCX connector
- Suitable for embedded applications



ADA-12 is a most compact GPS antenna module in the market. It's specially designed for the portable device that needs GPS antenna embedded such as PND, laptop, mobile phone and so on. Also, ADA-12 is compatible with most GPS receives available on the market and provides a perfect alternative for the application of the GPS in different fields.

Specification

Category	GPS		
Frequency	1575.42 ± 3 MHz		
Polarization	R.H.C.P.		
Antenna Gain	Typ. 1.0 dBic		
Bandwidth	5 MHz min @S11-10 dB.		
	LNA		
Amplifier Gain	Typ 17 dB		
Noise figure	Typ 1.3 dB		
Output Impedance	50 Ω		
VSWR	< 2.0:1		
	Electrical Specifications		
Supply Voltage	3.0 VDC		
Power consumption	3.9 mA (3.0 VDC)		
Total Gain	16 dB		
Impedance	50 Ω		
VSWR	< 2.0 : 1		
RF Cable	5 cm OD 1.13 (std)		
Connector	U.FL. (std)		
	Overall Performance		
GPS part size	12 x 12 x 6.25 mm		
Weight	5 ± 0.5 grams		
Mounting	Sticky tape		
Operating temperature	-40 — +85 ° C		
Storage temperature	-40 — +85 ° C		

Ordering codes

TYPE	Description	Comment
ADA-12	Cable Length and Connector	GPS antenna module

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied. Adactus products are not authorized as critical components in life support devices or systems.