

ADA-12J

GPS Small Patch Antenna

- GPS Active Antenna
- 25dB Gain
- High Sensitivity
- Low current consumption
- Dual Voltage
- Suitable for embedded applications

ADA-12J is a most compact GPS antenna module in the market. It's specially designed for the portable device that needs GPS antenna embedded such as PND, laptop, mobile phone and so on. Also, ADA-12J is compatible with most GPS receives available on the market and provides a perfect alternative for the application of the GPS in different fields.



Specification

Category	GPS		
Frequency	1575.42 ± 3 MHz		
Polarization	R.H.C.P.		
Antenna Gain	Typ. 1.0 dBic		
Bandwidth	5 MHz min @S11-10 dB.		
	LNA		
Amplifier Gain	Typ 25 dB		
Noise figure	Typ 1.5 dB		
Output Impedance	50 Ω		
VSWR	< 2.0:1		
	Electrical Specifications		
Supply Voltage	2.8-3.7 VDC		
Power consumtion	6.5 mA (3.0V DC)		
Total Gain	25 dB		
Impedance	50 Ω		
VSWR	< 2.0 : 1		
RF Cable	5cm OD 1.13 (std)		
Connector	U.FL (std)		
	Overall Performance		
GPS part size	12 x 12 x 6.5 mm		
Weight	5 ± 0.5 grams		
Mounting	Sticky tape		
Operating temperature	-40 — +85 ° C		
Storage temperature	-40 — +85 ° C		

Ordering codes

ТҮРЕ	Description	Comment
ADA-12J	Cable Length and Connector	GPS Patch antenna

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein. This publication supersedes and replaces all information previously supplied.

Adactus products are not authorized as critical components in life support devices or systems.