

ISM Band Antenna

- ISM Antenna
- Weather Proof
- External
- 2 dBi Gain
- Tilttable



ADA-0176 is an ISM band antenna with through hole mounting and with a flying lead terminated with a U.FL type connector or connector of customer choice. Suitable for mobile wireless communication devices. The antenna can be folded when not in use. Omnidiradiant performance.





Specification

Antenna	Specification
Frequency	868MHz
Polarization	Vertical
V.S.W.R	<2.0:1
Impedance	50Ω
Return Loss	See Diagram
	Environmental Conditions
Operating Temperature	-20°C ~ +60°C
Storage Temperature	-30°C ~ +70°C
Relative Humidity	40% to 95%
	Mechanical Specification
Antenna Color	Black
Cable	RG178, 100mm
Connector	I-PEX
Size	103mm
Weight	5g Max.
Mounting	Through Hole Mount

Return Loss & VSWR





Ordering codes

TYPE	Description	Comment
ADA-0176-868	External ISM Antenna	868Mhz Antenna

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied. Adactus products are not authorised as critical components in life support devices or systems.