
Multi Frequency Band Antennas

- High Speed Internet
- Vehicle tracking
- Asset tracking
- GPS/Glonass Navigation
- Telemetry
- 4G/Lte
- GPS/Glonass

ADA-X4XX is a range of multi-frequency antennas for 2G, 3G, 4G/Lte, GPS, GPS/Glonass, WiFi.

The ADA-X4XX antennas are available in centre bolt, magnet mount as well as adhesive tape mount versions.




RoHS

**Lte**TM


Specification

Category	GPS	GPS/Glonass
Frequency	1575.42 MHz	1575.42 MHz & 1602 MHz
Polarization		R.H.C.P.
Power Gain		Typ. 27 dB
Noise figure		Typ. 1.5
Attenuation	Min. 20 dB @ Fo ± 50 MHz	
Bandwidth	2 MHz	10MHz & 8 Mhz
Output Impedance	50 Ω	
VSWR	<= 2.0	
Supply Voltage / Current	2.5 – 5.5 VDC / 12-20 mA	
RF Cable	Standard 3 m RG174/U with standard connector	
	GSM/UMTS/2400	
Frequency	824 ~ 960 MHz (GSM 850/900MHz) 1710 ~ 1990 MHz (GSM 1800/1900MHz) 1922 ~ 2170 MHz (3G 2100 MHz) 2400 ~ 2483 MHz (2400 MHz) 704 ~ 9660 - 1710 ~ 2620MHz(4G Lte)	
Polarization	Vertical Linear	
Gain	850 MHz= 1.0 dBi 900 MHz= 1.0 dBi 1800 MHz= 1.0 dBi 1900 MHz= 1.0 dBi 2100 MHz= 0.0 dBi 2400 MHz= 0.0 dBi	
Impedance	50 Ω	
VSWR	<= 2.0	
Power	10 W	
RF Cable	Standard 3 m RG174/U with standard connector	
	Overall Performance	
Size	63 x 15.6 mm (D x H)	
Mounting	Centre bolt 12,7 x 19mm, Magnetic or Tape	
Operating temperature	-40 — +80 ° C	
Storage temperature	-45 — +100 ° C	
Protection Rating	IPX7	


850MHz




1900MHz




900MHz




2100MHz




1800MHz



2400MHz





Ordering codes

TYPE	GPS	850	900	1800	1900	2100	2400 WiFi	No of cables
ADA-0410-x			X	X				1
ADA-0420-x		X			X			1
ADA-0430-x		X	X	X	X			1
ADA-0440-x		X	X	X	X	X		1
ADA-0450-x		X	X	X	X	X	X	2
ADA-0460-x							X	1
ADA-1410-x	X		X	X				2
ADA-1420-x	X	X			X			2
ADA-1430-x	X	X	X	X	X			2
ADA-1440-x	X	X	X	X	X	X		2
ADA-1450-x	X	X	X	X	X	X	X	3
ADA-1460-x	X						X	2
ADA-1470-x	X							1
ADA-0480-x		704 ~ 960MHz			1710 ~ 2620MHz			1
ADA-1480-x	X	704 ~ 960MHz			1710 ~ 2620MHz			2

If you want GPS/Glonass change the first digit to 2

x = C for Centre bolt mount
 S for Magnetic mount
 T for Tape (adhesive) mount

Example: ADA-2460-T means GPS/Glonass + WiFi +Tape mount

The antennas are delivered with different antenna cable lengths and different connectors. Contact Adactus or our distributor for a quote on any particular specification.

For the latest updates, visit our Web site: www.adactus.se

Disclaimer

Information furnished is believed to be accurate and reliable. However, Adactus assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Adactus reserves the right to make changes without further notice to any product herein to improve reliability, function or design. Adactus does not assume any liability arising out of the application or use of any product described herein.

This publication supersedes and replaces all information previously supplied. Adactus products are not authorised as critical components in life support devices or systems.