

## High Frequency Mounts

3/4" hole; 1-1/8"-18 thread; Crimp on



MMF



MMF-VP



MLFML195C



GMLFML195C

Model	Mount Type	Coax	Connector
MMF	Permanent microwave mount for frequencies from 800 MHz to 6.0 GHz. Accomodates thickness up to .06 inches.	None	Male SMA*
MMF-VP	Vandal-proof mount for frequencies from 0 GHz to 6 GHz. Accomodates surfaces up to .09-inch thick.	None	Male SMA
MLFML195C	Permanent mount for frequencies from 800 MHz to 6.0 GHz. Accomodates thickness up to 0.046 inches.	17 ft. Pro-Flex™ Plus 195	Loose TNC male standard. Contact customer service for other connector options.
GMLFML195C	Magnetic base mount for frequencies from 800 MHz to 6.0 GHz.	12 ft. Pro-Flex™ Plus 195	Attached TNC male standard. Contact customer service for other connector options.
MLFPP240C	Permanent mount for frequencies from 800 MHz to 6.0 GHz. Accomodates thickness up to 0.046 inches.	17 ft. Pro-Flex™ Plus 240	Loose TNC male standard. Contact customer service for other connector options.

## High Frequency Mounts For Thick Roof Surfaces

5/8" hole; 1-1/8"-18 thread; Crimp on

Model	Mount Type	Coax	Connector
MVPHP	Vandal-proof permanent mount for frequencies from 900 MHz to 6 GHz. Accomodates thickness up to 1/2-inch.	None	M to N Female*