Product Datasheet
AD910J



AD910J

RCBO 1P+N 6kA B-10A 30mA A Class

Technical Features

Architecture	
Type of pole	1P+N
Number of protected poles	1
Curve	B
Electric current	
Rated current IN	10 A
Rated residual operating current Idn	30 mA
Rated current at -25°C	12.06 A
Rated current at -20°C	11.88 A
Rated current at -15°C	11.69 A
Rated current at -10°C	11.5 A
Rated current at -5°C	11.31 A
Rated current at 0°C	11.13 A
Rated current at 5°C	10.94 A
Rated current at 10°C	10.75 A
Rated current at 15°C	10.56 A
Rated current at 20°C	10.38 A
Rated current at 25°C	10.19 A
Rated current at 30°C	10 A
Rated current at 35°C	9.85 A
Rated current at 40°C	9.71 A
Rated current at 45°C	9.56 A
Rated current at 50°C	9.41 A
Rated current at 55°C	9.26 A
Rated current at 60°C	9.12 A
Correction factor of rating current for 2 devices placed side by side	1
Min./max. threshold value of the AC thermal operation	1.13 - 1.45 A
Safety	
Residual current type	A
Ingress Protection (IP) class	IP2X
Main electrical attributes	
Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	6 kA
Voltage	
Rated insulation voltage Ui	500 V
Electric current	
Rated service breaking capacity Ics AC according to IEC 60898-1	6 kA
Voltage	
Rated impulse withstand voltage Uimp	4000 V
Max. operating voltage	240 V
Rated operational voltage Ue	240 - 240 V
Overvoltage category according to IEC 60947-1	3
Type voltage supply	AC
Power	
Power dissipation at IN	3.40 W
Frequency	
Frequency	50 - 50 Hz
Use conditions	
Max. altitude	2000 m

Installation, mounting	
Nominal tightening torque down terminal	2.10 - 2.10 Nm
Nominal tightening torque top terminal	2.10 - 2.10 Nm
Use conditions	
Class of energy limitation I^2t	3
Endurance	
Electric endurance in number of cycles	2000
Number of mechanical operations	2000
Connection	
Cross-section flexible conductor	1 - 16 mm^2
Cross-section rigid conductor	1 - 25 mm^2
Cross-section of input with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input with screws, for massive conductors	1 - 25 mm^2
Capacity	
Number of modules	2
Installation, mounting	
Type of bottom connection for modular devices	biconnect
Dimensions	
Height	83 mm
Width	35 mm
Depth	68 mm
Use conditions	
Operating temperature	-25 - 40 °C
Storage/transport temperature	-25 - 70 °C
Connection	
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input and output with screws, for massive conductors	1 - 25 mm^2
Use conditions	
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Air humidity protection	For all climates
Sustainability	
RoHS conform	Yes