
Product Datasheet
AEA925T



AEA925T

RCBO 1P+N 6kA C-25A 100mA A

Technical Features

Architecture

Type of pole	1P+N
Number of protected poles	1
Curve	C

Electric current

Rated current IN	25 A
Rated residual operating current Idn	100 mA
Rated current at -25°C	28.25 A
Rated current at -20°C	27.95 A
Rated current at -15°C	27.66 A
Rated current at -10°C	27.36 A
Rated current at -5°C	27.07 A
Rated current at 0°C	26.77 A
Rated current at 5°C	26.48 A
Rated current at 10°C	26.18 A
Rated current at 15°C	25.89 A
Rated current at 20°C	25.59 A
Rated current at 25°C	25.3 A
Rated current at 30°C	25 A
Rated current at 35°C	24.76 A
Rated current at 40°C	24.51 A
Rated current at 45°C	24.27 A
Rated current at 50°C	24.02 A
Rated current at 55°C	23.78 A
Rated current at 60°C	23.53 A
Correction factor of rating current for 2 devices placed side by side	1
Min./max. threshold value of the AC thermal operation	1.13 - 1.45 A

Safety

Residual current type	A
Ingress Protection (IP) class	IP20

Main electrical attributes

Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	6 kA

Voltage

Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4000 V
Max. operating voltage	240 V
Rated operational voltage Ue	230 - 240 V
Overvoltage category according to IEC 60947-1	3
Type voltage supply	AC
Dielectric strength value of power frequency	2 kV

Power

Power dissipation at IN	6.70 W

Frequency

Frequency	50 - 50 Hz

Use conditions

Max. altitude	2000 m

Installation, mounting

Nominal tightening torque down terminal	2.10 - 2.10 Nm
Nominal tightening torque top terminal	2.10 - 2.10 Nm

Use conditions	
Class of energy limitation I^2t	3
Endurance	
Electric endurance in number of cycles	2000
Number of mechanical operations	4000
Connection	
Cross-section flexible conductor	1 - 16 mm^2
Cross-section rigid conductor	1 - 25 mm^2
Cross-section of input with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input with screws, for massive conductors	1 - 25 mm^2
Capacity	
Number of modules	2
Installation, mounting	
Type of bottom connection for modular devices	biconnect
Dimensions	
Height	83 mm
Width	35 mm
Depth	68 mm
Use conditions	
Operating temperature	-25 - 40 °C
Storage/transport temperature	-25 - 70 °C
Connection	
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm^2
Cross-section of input and output with screws, for massive conductors	1 - 25 mm^2
Compatibility	
Suitable for DIN Rail	Yes
Use conditions	
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Sustainability	
RoHS conform	Yes