Product Datasheet
ST303



ST303

Bell transformer 8VA 230V 8-12V

Technical Features

Voltage	
Output voltage	8 - 12 V
Rated operational voltage Ue	230 - 230 V
Output voltage 2	12 V
Capacity	
Number of modules	2
Power	
Power consumption (VA)	8 VA
Power	8 VA
Power absorbed	8 W
Dimensions	
Height	111 mm
Width	35 mm
Depth	65 mm
Dimensions	111 x 35 mm
Safety	
Ingress Protection (IP) class	IP20
Temperature protection	Yes
Equipment	
Is short-circuit protected	Yes
On/off switch	No
Voltage	
Rated insulation voltage Ui	4000 V
Use conditions	
Operating temperature	-20 - 35 °C
Connection	
Cross-section flexible conductor	4 mm^2
Cross-section rigid conductor	6 mm^2
Frequency	
Frequency	50 - 50 Hz
Electric current	
Intensity output 1	1 A
Intensity output 2	0.67 A
Rated secondary current (Isr)	1 A
Installation, mounting	
Mounting on	DIN rail
Nominal tightening torque	1.20 - 1.20 Nm
Compatibility	
Suitable for DIN Rail	Yes
Sustainability	
REACh-SVHC free	Yes
RoHS conform	Yes

Illustrations | Drawings

