Product Datasheet
VE212R



VE212AK

Enclosure,vectorII,IP55,24M

Technical Features

Voltage	
Nominal voltage	400 - 400 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Surface mounting
Electric current	
Rated current IN	63 A
Equipment	
Number of rails	2
Number of rows	2
Number of section in width	1
With lock	No
Has neutral terminal block	Yes
Capacity	
Number of modules	24
Functions	
With conduit inlets	Yes
Dimensions	
Height	427 mm
Width	310 mm
Depth	151 mm
Cover, door	
Number of cabinet doors	1
Number of locks	0
Dimensions	
Number of width units	12
Cover, door	
Door/cover is transparent	Yes
Cabinet door type	Single door
Connection	
Number of conduit inlets	12
Materials	
Material	Plastic
RAL code	7035
Colour	Light grey
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No
Materials	
Ultraviolet-resistant	No
Safety	
Protection class	Isolation class II
Impact resistance IK	IK08
Ingress Protection (IP) class	IP65
Locking type	Snap on lock Without lock
Glow wire test	750 °C

Safety	
Protection class with door	IP65

Sustainability	
RoHS conform	Yes