# Product Datasheet
XVU107SCT-MO





XVR107S

**EV-Charging Station 7kW 1ph socket with CT 3ph one MONTA**

## Technical Features

| | |
|---|---|
| **Power** | |
| Power per charging point | 7 kW |
| Connected load | 0.1-7 kW |
| **Frequency** | |
| Frequency | 50 - 60 Hz |
| **Power supply** | |
| Number of phases for power supply | 1 |
| **Electric current** | |
| Rated current IN | 32 A |
| **Connectivity** | |
| Number of charging points | 1 |
| **Functions** | |
| With load management | Yes |
| **Equipment** | |
| Number of house sockets | 0 |
| With circuit breaker | No |
| With emergency release at power failure | Yes |
| **Connection** | |
| Connector/plug type | Type 2S |
| **Dimensions** | |
| Dimensions | 370 x 250 mm |
| Height | 370 mm |
| Width | 250 mm |
| Depth | 150 mm |
| **Installation, mounting** | |
| Mounting on | Wall mounting |
| **Safety** | |
| Ingress Protection (IP) class | IP55 |
| Impact resistance IK | IK10 |
| **Use conditions** | |
| Operating temperature | -25 - 50 °C |
| **Voltage** | |
| Nominal voltage | 220-240 V |
| **Materials** | |
| Material | Plastic |

## Illustrations | Drawings




| | |
|---|---|
| a (mm) | 370 |
| b (mm) | 250 |
| c (mm) | 150 |