

IP CCTV / Professional IP cameras / Hikvision / Dome Cameras

HWI-D149HA

HIWATCH



Features

- Hikvision
- Vu Color IP Dome Camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- White light range 30 m
- ColorVu: Color Image 24/7
- H.265+/H.265/H.264+/H.264
- Dual stream
- WDR (120 dB)
- 3D-DNR
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- Weatherproof IP67
- Vandal proof IK08
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	20 fps (2560x1440), 25 fps (1920x1080, 1280x720)
Extra Stream rate	25 fps (1280x720, 640x480, 640x360)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	96° (H), 52° (V), 113° (D)
Range performance	64 m (D), 25 m (O), 12 m (R), 6 m (I)
Minimum illumination	0.001 Lux @(F1.0, AGC ON)
Lighting	0 lux, White light 30 range [%VAR%] m
Image improvements	WDR (120 dB), BLC, HLC, 3D-DNR, AGC, AWB, Privacy Masking, ROI
Motion Detection	Supports human and vehicle detection
Alarms	Does not have
Audio	Does not have
Network interface	Ethernet 10/100 BaseT
Internal memory	Does not have
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 400 mA / 5W Max., PoE IEEE802.3af
Degree of protection	Weatherproof IP67, Anti-vandal IK08
Material	Base: Aluminium alloy Cover: Plastic

Temp. operation	-30° C ~ +60° C
Dimensions	97.6 (H) x 121.5 (Ø) mm
Base dimensions	Ø base 121.5 mm / Ø between bolts 104.7 mm / 3 bolts
Weight	500 g