

IP CCTV / Professional IP cameras / Hikvision / Dome Cameras

HWI-D620H-Z

HIWATCH



Features

- Hikvision HiWatch Series
- IP camera
- 1/2.8" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8~12 mm motorised varifocal autofocus lens
- 0 Lux
- IR Range 30 m
- H.265+/H.265/H.264+/H.264
- Dual stream
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- SD card recording
- Weatherproof IP67
- IR Cut
- WDR (120dB)
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	1080p / 720p (25 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm ~ 12 mm Motorised Autofocus
Minimum illumination	Colour 0.01 Lux @ F1.2 Colour 0.018 Lux @ F1.6
Infrared lighting	0 Lux / EXIR LEDs IR (30 m)
Image improvements	WDR (120dB), BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	Does not have
Audio	Does not have
Network interface	Ethernet 10/100 BaseT
Internal memory	Slot for MicroSD card, Max 128 GB
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 800 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67, Vandal-proof IK10
Material	Metal and Plastic
Temp. operation	-30° C ~ +50° C
Dimensions	99.6 mm (D) x 141.2 (Ø) mm

Weight

830 g
