

IP CCTV / Professional IP cameras / Safire Smart / Bullet Cameras

SF-IPB080A-8B1-DL

SAFIRE SMART



Features

- Safire Smart
- Range B1 with dual light
- Bullet IP camera
- 1/2.7" Progressive Scan CMOS
- 8 Megapixel (3840×2160)
- 2.8 mm Lens
- Minimum illumination 0.01 Lux@F1.6 ON | 0 Lux with IR
- DualLight scope 20~30m
- Compression H.265+ / H.265 / H.264+ / H.264
- 120 dB WDR
- 3DNR
- Integrated microphone
- MicroSD card slot up to 256 GB
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 with dual light
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840×2160)
Minimum illumination	Colour: 0.01 Lux @(F1.6 ON), 0 Lux with IR
Dual Light	IR and White Light Range: 20~30 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	8MP/6MP/4MP/2K/1080P (60Hz: 1~20fps; 50Hz: 1~20fps)
Extra Stream rate	720P/D1/VGA/640× 360 /480× 240/CIF (60Hz: 1~20fps; 50Hz: 1~20fps)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Bitrate	64 Kbps ~ 10 Mbps
Lens	2.8 mm
Field Of View (FOV)	H: 106.5°, V: 58.5°, D: 124°
Range performance	77 m (D), 31 m (O), 15 m (R), 8 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
MicroSD card slot	Up to 256 GB
Audio	Integrated microphone
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	Does not have
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF

Power	DC 12 V / 6.9 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Temp. operation	-30° C ~ +60° C
Dimensions	74.6 (H) x 75 (W) x 167.6 (D) mm
Weight	416 g