

IP CCTV / Professional IP cameras / Safire Smart / Turret cameras

SF-IPT010A-2B-DL

SAFIRE SMART



Features

- Safire Smart
- B1 Economic with dual illumination
- Turret IP Camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux
- Dual Light: IR range 30 m and White LED range 20m
- Compression H.265 / H.264
- WDR
- 3DNR
- Integrated microphone
- Audio
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1 Economic with dual illumination
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	Colour: 0.003 Lux @(F1.0, AGC ON) Night Color, color image 24/7h
Lighting Scope	Dual lighting: IR up to 30m White LED up to 20m Auto / Manual * Auto: When the camera detects the presence of a person, it switches from black and white mode to color mode, activating its white light
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	25 FPS (1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265 / H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8mm mm fixed
Field Of View (FOV)	H: 95°, V: 55°, D: 109°
Range performance	41 m (D), 17 m (O), 8 m (R), 4 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror (Mirror function)
SMD (Smart Motion Detection)	Smart Motion Detection: Supports human-based motion detection
Smart Features	Line crossover and area intrusion region based on human detection Smart Events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	Built-in microphone, 1 Input
Audio Compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT



Internal memory	Does not have
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power supply	PoE IEEE802.3af, max 5,5 W
P2P	Yes
Degree of protection	Weatherproof IP67
Temp. operation	-20° C ~ +55° C
Dimensions	84.8 (H) x 113.8 (Ø) mm
Weight	300 g