



Powermax30[®] XP

Professional-grade plasma system for handheld cutting 10 mm (3/8") metal.



Capacity	Thickness	Cut speed
Recommended	Cutting	
	10 mm (3/8")	500 mm/min (20 ipm)
	12 mm (1/2")	250 mm/min (10 ipm)
Severance	16 mm (5/8")	125 mm/min (5 ipm)

Easy-to-use, two-in-one design

- High-power cutting on thick metal plus FineCut[®] consumables for detailed, thin metal cutting.
- Plug into any 120 or 240 V power with Auto-Voltage[™] technology and included plug adapters.

Finish jobs faster

- 50% increase in cutting power* for fast cut speeds.
- Less edge preparation – patented consumables designs provide superior cut quality.
- Twice the consumable life* and 70% more efficient on average for lower cost of cutting.


Rugged and reliable

- New Duramax[™] LT torch designed to withstand impact and heat.
- Hypertherm Certified[™] reliability ensures performance in the most demanding environments.
- Optional durable carrying case protects the system and gear.



Duramax LT hand torch

Relative cut performance on mild steel



*compared to Powermax30

System includes

- Power supply, 4,5 m (15') Duramax LT hand torch with standard consumables, 4,5 m (15') work clamp
- Operator and safety manuals
- Consumable kit with 1 standard nozzle, 1 electrode, 1 FineCut nozzle and 1 FineCut deflector
- Plastic carry case
- Carrying strap

Ordering information


Power supply	System part number with 4,5 m (15') Duramax LT torch	System part number with 4,5 m (15') Duramax LT torch and carry case
120–240 V	088081	088080

Torch consumable parts

Consumable type	Torch type	Amperage	Shield/Deflector	Retaining cap	Nozzle and electrode pack	Swirl ring
Standard	Hand	30	420116	420114	428243 ¹	420211
FineCut	Hand	30	420115		428244 ²	

¹ Includes 2 standard nozzles (420118) and 2 electrodes (420120).

² Includes 2 FineCut nozzles (420117) and 2 electrodes (420120).



All-in-one consumable kit

All-in-one kits provide a sampling of all of the consumables available for your Powermax system. Experience the versatility of your system, while purchasing consumables at lower cost.

851390 Powermax30 XP kit

Specifications

Input voltages	120-240 V, 1-PH, 50/60 Hz
Input current @ 3,8 kW	120-240 V, 1-PH, 25-18,8 A
Output current	15-30 A
Rated output voltage	125 VDC
Duty cycle @ 40° C	35%, 240 V 20%, 120 V
Open circuit voltage (OCV)	256 VDC
Dimensions with handles	356 mm (14.0") D; 168 mm (6.6") W; 305 mm (12.0") H
Weight w/4,5 m (15') torch	9,7 kg (21.4 lbs)
Gas supply	Clean, dry, oil-free air or nitrogen
Recommended gas inlet flow rate/pressure	113,3 l/min (4 scfm) @ 5,5 bar (80 psi)
Input power cable length	3 m (10')
Power supply type	Inverter – IGBT
Engine drive requirement	5,5 kW for full 30 A output
Certifications	CSA-certified for use in the Americas and Asia, except China.
Warranty	Power supply: 3-year Torch: 1-year

Cutting with 120 V input power

Use FineCut nozzle and deflector for cutting at 120 V input power. When operating at the maximum recommended output of 25 A, the cut capacities are:

- 6 mm (1/4") at 482 mm/min (19 ipm)
- 10 mm (3/8") at 203 mm/min (8 ipm)
- 12 mm (1/2") at 76 mm/min (3 ipm)

Common applications

HVAC, mining, property/plant maintenance, fire and rescue, general fabrication, plus:



Agricultural



Vehicle repair and modification

Recommended Hypertherm genuine accessories



Face Shield

Clear face shield with flip-up shade for cutting and grinding. Safety shield included. ANSI Z87.1, CSA Z94.3, CE

127239 Face shield shade 6

127103 Face shield shade 8



Air filtration kit

A ready-to-install kit with a 1-micron filter and an auto drain moisture separator protects against contaminated air.

128647 Eliminizer filter



Durafit cutting gloves

Designed to offer maximum dexterity and fine-motor control. Fire resistant goatskin leather and stretch Nomex® backhand. Reinforced leather in wear areas.

017037 Medium

017038 Large

017039 X-large

017040 2X-large



System dust covers

Made from a flame-retardant vinyl, a dust cover will protect your Powermax system for years.

127144 Cover, Powermax30/30 XP



Circle cutting guides

Quick and easy set up for accurate circles up to 70 cm (28") diameter. For optional use as a stand-off guide for straight and bevel cuts.

127102 Basic kit – 38 cm (15") arm, wheels and pivot pin

027668 Deluxe kit – 28 cm (11") arm, wheels, pivot pin, anchor base and plastic case



System carry case

Rugged case for protecting and storing the Powermax30 or 30 XP and accessories.

127410 Case, Powermax30/30 XP

Engineered and assembled in the USA

ISO 9001:2008

Environmental stewardship is a core value of Hypertherm. Our Powermax products are engineered to meet and exceed global environmental regulations including the RoHS directive.



Hypertherm, Powermax, Duramax and FineCut are trademarks of Hypertherm Inc. and may be registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

© 1/2014 Hypertherm Inc. Revision 0
86047D

Hypertherm®
Cut with confidence®

