

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)



Revision: 07.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **Ceramic spray**
- UFI: XC00-60HM-3004-GP0C
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Identified use: intended for professional use only!
- Application of the substance / the mixture Coating
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: ABICOR-BINZEL (UK) Ltd. Mill Lane
Winwick Quay, Warrington WA28UA UK
Contact Person: Kevin Chudley
Email: kevin.chudley@binzel-abicor.co.uk
Contact Number: 01925 653944
- Further information obtainable from: Technical Documentation
- 1.4 Emergency telephone number: Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - STOT SE 3 H336 May cause drowsiness or dizziness.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
 - The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms

GHS02
GHS07
- Signal word
 - Danger
- Hazard-determining components of labelling: acetone
- Hazard statements
 - H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - P210 Keep away from sparks. - No smoking.
 - P251 Do not pierce or burn, even after use.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P405 Store locked up.
 - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Precautionary statements
 - Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.
 - Buildup of explosive mixtures possible without sufficient ventilation.
- Additional information:
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Determination of endocrine-disrupting properties

78-93-3 | butanone
List II

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture: consisting of the following components.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 1)

- Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥2.5-<10%

- Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact:

Seek medical treatment.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

- After swallowing:

Seek medical treatment.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

- 5.2 Special hazards arising from the substance or mixture

CO2

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

- 5.3 Advice for firefighters

- Protective equipment:

Do not inhale explosion gases or combustion gases.

- Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid contact with skin and eyes

Keep away from ignition sources.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 2)

- 6.4 Reference to other sections

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility:

Store away from foodstuffs.

- Further information about storage conditions:

Store in dry conditions.
Keep container tightly sealed.
Protect from heat and direct sunlight.
Recommended storage temperature: 5-30 °C

- Storage class:

2 B

- 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

- Regulatory information

WEL: EH40/2020

- Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

- Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 3)

- Hand protection



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye/face protection



Tightly sealed goggles

- Body protection:

Protective goggles and facial protection - Classification according to EN 166
protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Physical state

Aerosol

- Colour:

White

- Odour:

Characteristic

- Odour threshold:

Not determined.

- Melting point/freezing point:

Undetermined.

- Boiling point or initial boiling point and boiling range

56 °C

- Flammability

Not applicable.

- Lower and upper explosion limit

- Lower:

1.5 Vol %

- Upper:

13 Vol %

- Flash point:

-17 °C

- Ignition temperature:

Not determined.

- Decomposition temperature:

Not determined.

- pH

Not determined.

- Viscosity:

- Kinematic viscosity

Not determined.

- Dynamic:

Not determined.

- Solubility

- water:

Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)

Not determined.

- Density and/or relative density

- Density at 20 °C:

0.73 g/cm³

- Relative density

Not determined.

- Vapour density

Not determined.

- 9.2 Other information

- Appearance:

- Form:

Aerosol

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 4)

- Important information on protection of health and environment, and on safety.

- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Not determined.
- Solvent separation test:
- VOC (EC) 93.83 %
- Change in condition
- Evaporation rate Not applicable.

- Information with regard to physical hazard classes

- Explosives Void
- Flammable gases Void
- Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated.
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Void
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)

78-93-3 butanone

Oral	LD50	2,193 mg/kg (rat) (OECD 423)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	mg/l (Skeletanema costatum)
	LC50/4 h	34 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 5)

- **Aspiration hazard**

Based on available data, the classification criteria are not met.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

78-93-3 | butanone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**
67-64-1 acetone

IC50	20,000 mg/l (rabbit)
LC50/96 h	7,500 mg/l (Leuciscus idus (Aland))
	5,540 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
EC50	8,300 mg/l (LEPOMUS MACROCHIRUS) (96h)
	7,500 mg/l (Selenastrum capricornutum) (96h)
EC50	>100 mg/l (daphnia) (48h)
LC 50	20,000 mg/l (rabbit)
LC50	12,600 mg/l (daphnia)
NOEC	1,700 mg/l (Pseudomonas putida)
NOEC	4,740 mg/l (Pseudokirchneriella subcapitata)

78-93-3 butanone

LC50	2,990 mg/l (Pimephales promelas) (96h; OECD 203)
EC50	1,972 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
EC50	308 mg/l (Daphnia magna) (48h; OECD 202)
EC0	1,150 mg/l (Pseudomonas putida) (16h; DIN 38412)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:**

Not applicable.

- **vPvB:**

Not applicable.

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**

- **Recommendation:**

Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA**

UN1950

- **14.2 UN proper shipping name**

- **ADR**

1950 AEROSOLS

- **IMDG**

AEROSOLS

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 6)

- IATA	AEROSOLS, flammable
- 14.3 Transport hazard class(es)	
- ADR	
	
- Class	2.5F Gases.
- Label	2.1
- IMDG, IATA	
	
- Class	2.1 Gases.
- Label	2.1
- 14.4 Packing group	
- ADR, IMDG, IATA	Void
- 14.5 Environmental hazards:	Not applicable.
- 14.6 Special precautions for user	Warning: Gases.
- Hazard identification number (Kemler code):	-
- EMS Number:	F-D,S-U
- Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- Segregation Code	
- 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
- Transport/Additional information:	
- ADR	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- Transport category	2
- Tunnel restriction code	D
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
- Directive 2012/18/EU	
- Named dangerous substances - ANNEX I	None of the ingredients is listed.
- Seveso category	P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements	150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements	500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2023

Version number 8 (replaces version 7)

Revision: 07.06.2023

Trade name: **Ceramic spray**

(Contd. of page 7)

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

67-64-1 acetone

- **Regulation (EC) No 273/2004 on drug precursors**

67-64-1 acetone

3

78-93-3 butanone

3

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

67-64-1 acetone

3

78-93-3 butanone

3

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- **Relevant phrases**

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:**

Technical Documentation

- **Date of previous version:**

30.11.2021

- **Version number of previous version:**

7

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- www.echa.europa.eu
- www.baua.de
IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- **Sources**

- *** Data compared to the previous version altered.**