

FEATURES		N90
ENGINE		
No. of Cylinders / Capacity (cc) / Missions Level		4/ 4088/ Stage V
After Treatment System		DOC + DPF + SCR (Ad-Blu)
Rated Engine Power (kw/Hp)		90
Rated Engine Speed		2200
Max. Torque (Nm)		375Nm @ 1400 Rpm
Aspiration		Turbo charged with Intercooler
Air Cleaner		Dual Stage Dry Type
Block Heater		○
Downdraft Exhaust Pipe		●
Fuel Tank Capacity (l)		80
TRANSMISSION		
12x12 Synchro Shuttle transmission		●
Minimum/Maximum Speed		0.51 kmph/ 29.90 Kmph
FRONT AXLE		
4WD Front Axle		●
Differential Lock		Mechanical
4WD Actuation		Mechanical 4WD
Brake Actuation		Mechanical
PTO		
PTO Type		Mechanical
540/540E		●
HYDRAULIC		
Hydraulic Pump Flow (LPM)		56
Open Centre Mechanical Draft Control		●
Liftomatic System		●
Lift Capacity (kg)		2500
Linkage Category		II
Self Locking TPL Linkages		○
Max. no. of Rear Remotes		2/3 (Opt.)
REAR HITCHES		
E-Marked Swinging Bar		●
CBM Ladder Hitch		○
Cuna (X Type & Y Type) Hitch		○
TRAILER BRAKES		
Without Trailer Brakes		●
Hydraulic Trailer Brakes (DHTB)		○

FEATURES		N90
ELECTRICALS (ROPS/CAB)		
Battery		130AH 800CCA
Alternator		120A
Button Operated Battery Cut off Switch, 3 Pin Socket, Seven Pin Trailer Socket		●
OPERATOR ENVIRONMENT		
Suspended Platform (with ROPS)		●
Normal Driver Seat w/o Armrest		●
Tiltable & Telescopic Steering		●
Front Mud Guards		○
Ballast Weights (31*6) Kg		○
Ballast Rear Weights (30*2) Kg		○
Cabin Air Conditioning (With HVAC)		○
CAT-IV Cabin		●
DIMENSIONS (ROPS/CAB)		
Wheelbase (mm)		2300
Overall Length (mm)		4305
Overall Width (mm)		1495
Overall Height (mm)*		2365
Front Track Width (mm)		1200
Rear Track Width (mm)		1070
Ground Clearance (mm)		265
Unladen Mass (Kg)		3230
STANDARD TYRES (ROPS/CAB)		
Bias Tyres (4WD)		280/70R18 & 360/70R28
OPTIONAL TYRES (ROPS/CAB)		
Radial Tyres (4WD)		210/95R18 & 360/70R28
		8.00-18 & 14.9-24
		260/70R16 & 360/70R24
		280/70R18 & 420/70R24
		280/70R18 & 380/85R24
		8x18 * 13.6X24

● Standard ○ Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.



Solis
N90

COMMAND & COMFORT,
PERFECTLY BALANCED
WITH CAT IV CABIN



Solis

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com

www.solistractors.com




N90

CAT-IV CAB

Solis 90 NT Stage V is a powerful narrow tractor built for precision farming. Designed to conquer tight rows with ease, it combines agility with speed, making every pass efficient. Its advanced CAT-IV cabin ensures superior operator safety with a pressurized, dust-free environment and unmatched comfort during long hours in the field.



KEY FEATURES



Long-Lasting Battery Performance

Built for endurance, the Solis 90 NT features a high-capacity battery system optimized for long operational cycles, delivering consistent performance and reliability throughout the year.

Timeless Design with CAT-IV Cabin

With the CAT-IV-certified cabin of the Solis 90 NT combining modern aesthetics with functional excellence, this cabin is built to keep harmful particulates out while offering maximum comfort.



Cutting-Edge S-COMMAND Center

The S-command center offers an operator-first interface with easy access to all major functions, reducing fatigue and improving overall performance during extended working hours.

S-BOOST Hydraulics

The S-boost hydraulics system is designed to handle heavy implements and precision-driven tasks with ease. With higher lifting capacity and improved flow rate, it ensures reliable performance.



High Performance with S-TECH Engine

Solis 90 NT features an advanced S-tech engine designed to meet the latest Stage V emission standards, ensuring consistent power delivery for demanding operations.

