

# Winder Instruction Manual

## MK 1B with: Auto-lock, Sample Wiper and Depth Gauge.



MK 1B with Auto-lock, Depth Gauge, Cable Wiper and Screw Sleeve Hook

ECHA23/SW/SS30MDG-WW

*Results that count*

## **Winder MK 1B (Depth Gauge, Auto-Lock, Cable Wiper)**

### **Introduction**

The MK 1B Winder is designed to be used for the manual sampling of bulk liquids such as various types of oil and water. MKD have a set of gears, which enable smooth and easy lifting and lowering of relatively heavy sampling devices. They can be held in either the left or right hand.

The latest development of the winders has a new winding handle, incorporating a new reel lock. This gives added safety, by ensuring that the winding reel locks automatically as soon as the operator releases the winding knob.

The stainless steel cable has a safe working load of 48 kg. This gives the winders a good safety margin when working with samplers, which typically weigh between 1 kg and 4 kg. The winder has been tested with a load of 10 kg.

As an option, the winder cable can be fitted with small stainless steel ferrules, to give an indication of the depth of the sampling device during operation or in the case of the MK1 B with Depth Gauge a "depth gauge".

The winder is fitted with an earthing strap, which enables the operator to make a good electrical connection between the winder and the tank structure. This, in turn, minimizes the risk of a build-up of static electricity.

The winder hook, to which the sampler is attached, can be one of two types:

- a) a screwed sleeve type, which secures samplers that have a shackle at the top end, or
- b) a "bayonet" type, which secures samplers that have a matching bayonet slot at the top end.

Both types of hook ensure electrical continuity right through the system, and minimize the risk of losing a sampler during operation.

It must be highlighted that, although the system is designed to provide a safe method of lowering and lifting sampling equipment, the winder must always be used in accordance with this instruction manual. The user must also take into account ISGOTT guidance, company circulars and other directives.

## Operating Instructions

1. While the winders are carried about or not in use, they are automatically locked, thanks to the locking mechanism incorporated into the winding handles.
2. Check the condition of the stainless steel cable where it joins the hook, for signs of possible wear or damage.
3. Attach the hook to the sampler: unscrew the sleeve to open the hook, insert the shackle of the sampler, and screw the sleeve down again, in order to ensure safe connection and electrical continuity.
4. Before lowering the sampler into the tank, make sure that the winder is connected electrically to the tank structure, using the earthing strap.
5. If desired the lower edge of the frame may be rested on the rim of the tank.
6. When ready to lower the sampler, reset the depth gauge, if necessary, to zero. Unlock the winder reel by squeezing the plastic winding knob against the spring pressure. Turn the winding handle, keeping a grip on the plastic knob, to lower and raise the sampler.
7. If the winding knob is released at any time during operation, the reel will automatically lock. This avoids any possibility of a sampler falling out of control into the tank.
8. To determine the depth of the sampler use the Depth Gauge counter to see how far the sampler has travelled. Due to the thickness of the cable on the winder a user adjustment is required to ensure the correct depth is sampled as follows:

Actual Depth of the Sampler (M)	Depth Counter Reading (M)
5	5.0
10	10.1
15	15.2
20	20.7
25	26.4
30	31.7

9. Once the required sampling depth has been reached, lock the reel by releasing the winding knob. If appropriate to the sampler in use, jerk the winder to apply a "snatch" to open the valve on the sampler.
8. While lifting the sampler, particularly if it is a heavy one, it may be helpful to rest the lower part of the winder frame or leg on the lip of the tank opening.

## WARRANTIES & LIABILITY

1. Subject to the conditions set out below the Seller warrants that the Goods will correspond with their specification at the time of delivery and will be free from defect in material and workmanship for a period of 12 months from the date of delivery.
2. The above warranty is given by the Seller subject to the following conditions:
  - a. The Seller shall be under no liability in respect of any defect in the Goods arising from any drawing design or specification supplied by the Buyer.
  - b. The Seller shall be under no liability in respect of any defects arising from fair wear and tear, willful damage, negligence, abnormal working conditions, failure to follow the Seller's instructions (whether oral or in writing), misuse or alteration or repair of the Goods without the Seller's approval.
  - c. The Seller shall be under no liability under the above warranty (or any other warranty, condition or guarantee) if the total price of the Goods has not been paid by the due date for payment.
  - d. The above warranty does not extend to parts, materials or equipment not manufactured by the Seller, in respect of which the Buyer shall only be entitled to the benefit of any such warranty or guarantee as is given by the manufacturer to the Seller.
3. Subject as expressly provided in these Conditions and except where the Goods are sold to a person dealing as a consumer (within the meaning of the Unfair Contract Terms Act 1977) all warranties, conditions or other terms implied by statute or common law are excluded to the fullest extent permitted by law.
4. Any claim by the Buyer which is based on any defect in the quality or condition of the Goods or their failure to correspond with the specification shall (whether or not delivery is refused by the Buyer) be notified to the Seller within 28 days of the date of delivery or (where the defect or failure was not apparent on reasonable inspection) within a reasonable time after discovery of the defect or failure. If delivery is not refused, and the Buyer does not notify the Seller accordingly, the Buyer shall not be entitled to reject the Goods. The Seller shall have no liability for such defect or failure, and the Buyer shall be bound to pay the price as if the Goods had been delivered in accordance with the Contract.
5. Where any valid claim in respect of any of the Goods which is based on any defect in the quality or condition of the Goods or their failure to meet specification is notified to the Seller in accordance with these Conditions, the Seller shall be entitled to replace the Goods (or the part in question) free of charge or, at the Seller's sole discretion, refund to the Buyer the price of the Goods (or a proportionate part of the price) but the Seller shall have no further liability to the Buyer.
6. Illustrations, performance details, methods of assembly and all other technical data in the advertising sales and technical literature issued by the Seller are based on experience and upon trials under Test Conditions and are provided for general guidance only. No such information shall form part of the Contract.
7. Except in respect of death or personal injury caused by the Seller's negligence, the Seller shall not be liable to the Buyer by reason of any representation, or any implied warranty, condition or other term, or any duties, common law, or under express terms of the Contract, for any consequential loss or damage (whether for loss or profit or otherwise) costs, expenses or other claims of consequential compensation whatsoever (and whether caused by the negligence of the Seller, its employees or agent or otherwise) which arises out of or in connection with the supply of the Goods or their use or resale by the Buyer, except as expressly provided in the Conditions.
8. The Seller shall not be liable to the Buyer or be deemed to be in breach of the Contract by reason of any delay in performing, or any failure to perform, any of the Seller's obligations in relation to the Goods, if the delay or failure was due to any cause beyond the Seller's reasonable control. Without prejudice to the generality of the foregoing, the following should be regarded as causes beyond the Seller's reasonable control:
  - a. Act of God, explosion, flood, tempest, fire or accident.
  - b. War or threat of war, sabotage, insurrection, civil disturbance or requisition.
  - c. Acts, restrictions, regulations, by-laws, prohibitions or measures of any kind on the part of governmental, parliamentary or local authority, import or export regulations or embargo.
  - d. Strikes, lockouts or other industrial actions or trade disputes (whether involving employees of the Seller or of a third party).
  - e. Difficulties in obtaining raw materials, labour, fuel, parts or machinery.
  - f. Power failure or breakdown in machinery.