

WELCOME GUIDE

Bullet 48 | OCC-73D |

PRODUCT OVERVIEW



Car Charger×1

BASIC PRODUCT SPECIFICATIONS

Model	OCC-73D
Input	DC 12~24V/5.0A
Single-Port Operation	USB-C1: 5.0V \Rightarrow 3.0A, 9.0V \Rightarrow 3.0A, 11V \Rightarrow 2.72A(Max) PPS: 3.3V~5.9V/3A; PPS:3.3V~11V/2.45A
	USB-A1: 5.0V \Rightarrow 3.0A, 9.0V \Rightarrow 2.0A, 12V \Rightarrow 1.5A
Dual-Port Operation	USB-C1: 5.0V \Rightarrow 3.0A, 9.0V \Rightarrow 3.0A, 11V \Rightarrow 2.72A(Max) PPS: 3.3V~5.9V/3A; PPS: 3.3V~11V/2.45A
	USB-A1: 5.0V \Rightarrow 3.0A, 9.0V \Rightarrow 2.0A, 12V \Rightarrow 1.5A
Total Output	USB-A+USB-C: 48W

*oraimo Lab test results

IMPORTANT SAFETY INSTRUCTIONS

1. The product is suitable for use together with IT equipment only.
2. The maximum ambient temperature during use of the appliance must not exceed 35°C.
3. Naked flame sources, such as candles, must not be placed on the product.
4. The disconnection from line voltage is made by an AC plug.
5. In case of broken cords or plugs, the product must be disposed of.
6. If you want to clean the product, use only a dry cloth or brush.
7. The power supply is not intended to be repaired by service personnel in case of failure or component defect (the product can be disposed of).