

For more information, please visit:





WELCOME GUIDE

PowerNova Q41 | OPB-7401Q |

* For safety issue, the power bank remains low capacity during shipping.
Please fully charge the battery before use!

(

IMPORTANT SAFETY INSTRUCTIONS

- Power bank can be recharged for an extended 1-2 hours after the first three full charges, which allowing the power bank to achieve optimal performance.
 Power bank can be fully recharged and discharged for the first three times to achieve optimal
- Power bank can be fully rechanged and discharged for the first three times to achieve optimal performance.

 Do not store the power bank in excessive heat or in a humid environment, such as in direct sunlight or near heating appliances, as it may cause an explosion.

 Using chargers or power supply units that are not recommended by or sold with the power bank may increase the risk of fire or personal injury.

 The permissible temperature range for using the power bank should be between 0°C and 45°C.

 Avoid disassembling, modifying, inserting any foreign objects into, or immersing in water or any liquid to prevent liquid leadage, overheating, fire or explosion.

 If the power bank is not in use for a long period of time, ensure it is recharged regularly once every three months, and it is recommended to store more than 50% of the power.

 When the power bank is recharged, some heat may be generated which is normal. No need to worry.

- When the power bank is recharged, some heat may be generated which is normal. No need to worry.

 Keep the power bank out of reach of children to prevent them from swallowing or entangling it. Furthermore, do not expose it to heat or fire.

 Cleaning the power bank should not be done with any harmful chemicals or detergents.

 Oversue, intense shocks or drops may cause damage to the power bank.

 Utilize only original or certified cables for connecting.

- W Real-time wattage

35 w

real-time charging power. Figure :

Fast charging mode activated

- mode activated 20W

 1. Press the main button to check the battery percentage on the digital screen.

 2. Charge your device through Z USB-A output ports and 2 Type-C output port.

 3. Recharge the power bank via either of the two Type-C input ports (Input 1 or Input 2). Both ports support simultaneous charging, with a combined maximum input power of 35W when used together. A Type-C charging cable is included in the package.

 4. The power bank will automatically shut down if no device is connected within 32 seconds.

 5. In charging mode, clouble press the power button to switch the LED display between battery percentage and real-time charging power.

 6. PowerNova Q41 automatically detects low-current mode, ideal for charging TWS earbuds, smartwatches, toothbrushes, and similar devices. The low-current charging mode will automatically turn off once the device is fully charged.

 7. Both Type-C ports support fast charging.

USAGE INSTRUCTIONS

- بعض امادة شمن بنك الطاقة لمدة 2-1 ساعات معتدة بعد أول ثلاث عمليات شمن كاملة، ما يسمح لبنك الطاقة بتحقيق (الأداء الأمثل).
 لا إمادة شمن وغريع بنك الطاقة بالكامل لأول كلاث مرات لتحقيق الأداء الأمثل.
 لا تحزي المساقة من وغريع بنك الطاقة بالكامل لأول كلاث مرات لتحقيق الأداء الأمثل.
 لا تحزيث في محيث المعتبر المساقة في من المعتبر المواجعة في المعتبر المباشر أو قريباً من أجهزة التنفقة.
 لمستخدام لجهزة الشمن أو وحدات المهدال الطاقة غير الموصعي بها لينك الطاقة بين وحدي المعتبر بها يودي إلى زيادة خطر من بنيا نهر بنا وحديث المعتبر المهدال المعتبر المهدال المعتبر المساقل الله أو حديث عليها.
 يعتب الكامل أول من طاقة برعل بالدافة أو المؤلف إلى المواجعة من المعتبر المساقل المها أو المعتبر المساقل الله أو المعتبر المعتبر

- ARI best at λ (10 (رائيس التعاق بن السبة للوقة البطارية على المثلثة الراهبة.

 2 (مدن جهاك عاد 2 سنّنا معرف ARS) 2 منظ معرف (10 (مدن المراق المراق المنظ المثلث المثنى المتراتب مع طالة إدخال Dype-C (مدن المراق المراق المنظ المثلث المثنى المتراتب مع طالة إدخال المنظ والمنظ المثنى المثنى المتراتب مع طالة إدخال المنظم المثنى والمثنى المثنى المثنى

- Main Button
Press to see the power level
22.5W
Output3 (USB-A)
22.5W
Output4 (USB-A)