

Plasson PP Ball Valve



Technical Catalogue

2008

General: Ball Valves, made of PP, intended to be used in various PE piping systems for potable water, irrigation, gardening etc.

Design features: • Polypropylene body and components • Excellent chemical resistance for a wide range of uses • Long term hydraulic resistance similar to the Plasson compression fittings range

- Full bore Bidirectional Compression (Plasson Series 7) and threaded outlets PTFE seat seals
 PN rating: 16 bar (based on the relevant standards, see below)
- Construction protected from accidental unscrewing of components by pipe rotation Removable handle
- The threaded versions of the valve can be rotated around the valve's axis after tightening in order to obtain the required handle position


Relevant standards: ISO 14236 (Compression Fittings) ■ ISO 5208 (Testing of plastic valves)

Recommended use: • House connection with Threaded Saddle, Tee, Manifold or EF Branch Saddle, before and after the mete • Boundary box (UK) • General purpose potable water, agriculture, irrigation, gardening

Global Presence - Local Commitment

E PLASSON®






d	dp*	z	Lp	н	F	J	К	W
20	15	41	55	151	48	67	52	150
25	20	50	55	160	60	78	60	200
32	25	62	62	186	70	80	78	350

Male Adaptor






dxG	dp*	Lt	z	Lp	н	F	J	К	w
20 x ¹ /2"	15	17	41	55	113	48	67	52	120
20 x 3/4"	15	18	41	55	114	48	67	52	125
25 x ³ /4"	20	18	50	62	123	60	78	60	160
25 x 1"	20	20	50	55	125	60	78	60	167
32 x 1"	25	20	62	55	144	70	80	78	280
32 x 1 ¹ /4"	25	23	62	62	147	70	80	78	290

Female Adaptor





dxG	dp*	Lt	z	Lp	н	F	J	К	W
20 x ¹ /2"	15	17	41	55	113	48	67	52	120
25 x ³ /4"	20	18	50	55	123	60	78	60	160
32 x 1"	25	20	62	62	144	70	80	78	280

^{*} Full Bore Dimensions

EPLASSON®

PLASSON Ltd. Maagan Michael, D.N. Menashe 37805 Israel Tel: +972-4-6394711, Fax: +972-4-6390887 E-mail: sales@plasson.com