

Climex Boiler MBR 250

This 250kW mobile boiler hire unit is capable of providing temporary heating and hot water.

It can be easily connected to existing pipe work using flexible hoses or a range of AHU's for a stand alone solution.

The 250kW boiler is supplied with an integrated heat exchanger and booster pump.

Features & Benefits

- ✓ Dual Fuel
- ✓ Efficient
- ✓ Indirect Fired
- ✓ Heating and Hot Water

Key Applications

- ✓ Local & National Government
- ✓ HVAC Contractors
- ✓ Schools
- ✓ Hotels
- ✓ Process Heating
- ✓ Factories
- ✓ Leisure Centres
- ✓ Marquee Heating with AHUs

Technical specifications

| | |
|--|---|
| Nominal Heating Capacity | 250kW @ 85°C |
| Fuel Consumption On Oil @ M.C.R. | 27.5 litres per hour |
| Fuel Consumption On Natural Gas @ M.C.R. | 14.6 mbar @ 28.5m ³ /hr 1/2" Gas Train |
| Heating Pump Flow Rate | 5.4 litres per second |
| Heating Expansion Tank Capacity | 200 Litres |
| Nominal DHW (Hotwater) Capacity | 250kW @ 55°C |
| DHW (Hotwater) Pump Flow Rate | 1.06 litres per sec (Max.3816 litres/h) |
| Control System | Automatic, time clock and frost stat |
| Noise Level | 52dB(A)@10m |
| Electrics | 230V 1PN & E |
| Plug | BS4343 3-pin 16amp |
| Flow / Return Connections | 2 Inch (Storz or BSP) |
| Dimensions LxWxH | 3200x2200x2000mm |
| Weight | 3198 Kg |

