

## DUSTEX® DustoMat 16

**High-performance extraction with fine filtration capacity and articulated arms for maximum dust capture.**

Cleanable cartridge filters ensure a filter system with a long service life and low operating costs. The patented tilt-back mechanism of the filter housing allows convenient disposal of the collected dust. Dust extraction from individual machines and manual work stations.

It can be connected to simple ductwork systems serving multiple machines. Specifically designed for the stone industry. For the extraction of hazardous dust types, especially mineral dust. Certification M, GS. Equipped with airflow pressure gauge and manual rotating compressed air filter cleaning system.

### Features & Benefits

- ✓ Certified for hazardous dust types
- ✓ High mobility
- ✓ Unique compressed air filter cleaning mechanism\*
- ✓ Low operating costs
- ✓ Patented tiltable filter section for easy dust disposal
- ✓ Compact design
- ✓ Available with adjustable arm for local capture

\* does not come with compressor

### Key Applications

- ✓ On site stone mason work stations (bankers shops)
- ✓ Stone façade repair works



## DUSTEX® DustoMat 16



\* Capture hood type may vary

### Technical Specifications

|                           |                      |
|---------------------------|----------------------|
| Motor                     | 1.1 kW               |
| Voltage                   | 115/230/415 V        |
| Max Airflow m3/hr         | 1140                 |
| Intake Diameter           | 125 mm               |
| Filter surface            | 9,4 m <sup>2</sup>   |
| Max Neg pressure          | 2000 Pa              |
| Dust collection container | 45 Litres            |
| Dimensions (L x W x H)    | 1470 x 670 x 1150 mm |
| Weight                    | 110 kg               |