DUSTEX® Hydramist 13

Airborne dust eliminator

Powerful and effective

Key Product Features

- 110 volt 2.2kw motor/2kva
- 32 amp plug
- Up to 13m coverage
- Tilting range 10º to 50º

Key Applications

- Demolition
- Removal of tiles, plaster, paint and cement
- Break up / cutting of road surfaces, paths and reinforced concrete
- Manufacturing processes
- Internal and external use

Easily transported and quick to set up, the Hydramist 13 is a powerful option for controlling airborne dust.

Sending a fine mist of water into the air, it quickly helps to suppress harmful dust, protecting the health of those nearby and helping to prevent damage to property and the environment.

The machine is simply connected to a mains water supply using a twist-fit connector and the angle of spray can be adjusted from 10˚ to 50˚.

DUSTEX®

DUSTEX Hydramist 13

Technical specifications	
Electric connection	2P+ T Socket 16A IP67
Electric motor	110 50Hz 2.2KW
Fan	6 nylon blades, aluminium hub
Air flow	90 m^3/min
Nozzles	Stainless steel, 12 connections
Water connection	Express type 1/2"
Water filter	300 microns
Nominal pressure	From 1 up to 5 bar
Tilting range	From 10° to 50°
Coverage	13 mt (without wind)
Dimensions (LxWxH)	985mm x 785mm x 835mm
Weight	77kg
Water consumption	
1.0 bar	3.6 L/min
1.5 bar	4.5 L/min
2.0 bar	5.0 L/min
2.5 bar	5.8 L/min