



BM25 Transportable Area Multi-Gas Detector

This gas detector is capable of monitoring from one to five gases through diffusion or sample draw.

The BM25 packs the benefits of a fixed -system area monitor into an easily transportable, yet rugged, instrument.

Features & Benefits

- ✓ Powerful audible alarm (103 dB @ 1 m) coupled with an ultra-bright visual alarm beacon produces clear warning
- ✓ Easily transportable - less than 7 kilos
- ✓ Simultaneous display of all gases monitored provides confidence and ease of use
- ✓ P66 Ingress Protection Rating

Key Applications

- ✓ Monitor gases in areas where workers may be at risk

Technical Specifications

Dimensions	470 x 180 x 190 mm
Weight	6.8 kg
Case Material	Impact resistant polycarbonate

Sensors

Our units are set up as area monitors for diesel exhaust emissions:
 Nitric oxide (NO)
 Nitrogen dioxide (NO₂)
 Carbon monoxide (CO)
 Carbon dioxide (CO₂)

Power

NiMH (170 hours maximum operating time, 100 hours typical) 4.5 hours typical

Safety Classifications

ATEX: II 1 G I EEx ia IIC T4; I M1 I EEx ia I or (when used with IR flameproof sensor), II 2 G I EEx ia d IIC T4; I M2 I EEx ia d I
IECEx: Ex ia IIC T4 I Ex ia (BM25 without IR sensor), Ex ia d IIC T4 I Ex ia I (BM25A without IR sensor) or, when used with IR flameproof sensor, Ex ia d IIC T4 I Ex ia d I (BM25 and BM25A)
CSA: Class I, Groups A, B, C, D, T4; Ex ia d IIC T4; C22.2 no. 152 (excluding aspirated, XP IR and PID sensor configurations)
INMETRO: BR-Ex iad IIIIC T4 (excluding XP IR and PID sensor configurations)

Alarms

103dB @ 1 metre
 Ultrabright LED beacon visible 360 degrees

