


NEBRASKA^{LITHIUM}

IP65 LED slim emergency bulkhead with a range of attachments



NEBRASKA SEMI-RECESSED MOUNTING KIT



GEAR TRAY FIXED TO DIFFUSER FOR FASTER INSTALLATION



STANDARD LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



"MAN RUNNING THROUGH DOOR" V2 LEGENDS AVAILABLE AS UP, DOWN, LEFT & RIGHT



SCAN FOR DIGITAL COPY

APPLICATIONS

- Corridors
- Exits
- Escape routes

CONSTRUCTION

- Polycarbonate base and cover
- Cover fitted to base with stainless steel screws in threaded brass inserts
- Gear tray fixed to diffuser for instant access to terminal block & fixing points for faster installation
- Supplied with standard ("Man running towards door") legend pack.
- 20mm conduit entry
- Lithium (LiFePO₄) battery cells (not suitable for use below 0°C)

TECHNICAL DETAILS

- 175 lm on mains
- 133 lm on battery supply
- 1.9W
- 3 hours operation on battery power after mains failure
- 20m maximum viewing distance with standard legends
- 30m maximum viewing distance with drop-down attachment
- Can be installed as maintained or non-maintained. Wiring diagrams are supplied in the instruction leaflet.

OPTIONS


DROP DOWN ATTACHMENT

Polycarbonate drop down signage attachment available, c/w legends. Order as separate item.


RECESSED MOUNTING KIT Semi-recessed mounting kit available. Cut-out 360 x 120mm. Order as a separate item.

LEGENDS Spare legend packs available. Alternative legend pack available as listed - to be ordered as a separate item. For "man running through door", use suffix V2, as listed.

NEBRASKA WITH DROP DOWN ATTACHMENT



NEBRASKA



ORDER CODE	DESCRIPTION
NNE/2/LED/M3/LITH/V3	Nebraska V3 2W LED IP65 Maint. 3Hr Lithium
ATTACHMENTS	
NNE/DDA/V3	Nebraska Drop Down Attachment C/W Legend Packs
NNE/RMK/V3	Nebraska V3 Recessed Mounting Kit
NNE/V2/LEP4	Nebraska V2 Legend Pack Of Up Down Left Right
NNELEP4	Nebraska Legend Pack Of Up Down Left Right