

Hayley LED Slim-Line Surface

SURFACE LUMINAIRES



Description

Where surface decorative downlighters are required our Hayley LED Slim-Line offers exceptional performance and creates a decorative appearance whilst keeping a low profile. IP54 as standard.

Application

- Offices
- Receptions
- Circulation Areas
- Toilets

Body & Finish

Formed from spun steel, complete with a high performance SLM heat sink to ensure life and lumen package. Frosted diffuser as standard.

Attachments

- Clear Diffuser
- Any Body Colour Available (White Body as Standard)



Hayley LED Slim-Line Surface

SURFACE LUMINAIRES

Order Codes

Wattage	Luminous Flux	lm/W	Diameter	Depth	Product Code
4.9 W	581 lm	118 lm/W	224 mm	21 mm	SGL/LED/700/HAY/SLIM/SUR

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

Sizes

- Diameter: 110 mm
- Depth: 60 mm



Control Gear

Tridonic/OSRAM

- Standard LED
- DALI Dimming LED
- WI-FI

Code Options

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming

Main Attributes

- Module efficacy up to 150lm/watt
- 50,000h L90 at 25°C
- Self Cooling
- Colour Rendering Index >80
- 7 Year Guarantee*
- CE Marked

* Please refer to the Warranty for more information.

LED Tape

- Tridonic/OSRAM LED Tape
- Colour Temperatures Available: 2200k/3000k/4000k/5000k/Tunable/RGB
- All LED data and performance data is taken at an ambient temperature of +25°C

Photometrics

-