

# Triton MKII LED

DOWNLIGHT LUMINAIRES



CE

LED

IP54

IK10

BIM



## Description

Where unobtrusive downlighters are required our Triton MKII LED offers exceptional performance where a decorative appearance is required. The recessed LED COB offers exceptional glare control. IP54 as standard.

## Application

- Offices
- Receptions
- Circulation Areas
- Toilets



## Body & Finish

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

## Attachments

- Bezel Available in Any RAL Colour
- Black Reflector
- IP65 Version



# Triton MKII LED

## DOWNLIGHT LUMINAIRES

### Order Codes

Wattage	Luminous Flux	lm/W	Diameter	Depth	Product Code
17.6 W	2254 lm	128 lm/W	110 mm	140 mm	SGL/LED/110/2500/TRI/MKII

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

### Sizes

- Diameter: 110/190/230 mm
- Depth: 100/127/140 mm
- Cutout: 95/165/205 mm

### Code Options

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming

### LED Boards

- Tridonic/OSRAM LED
- Colour Temperatures Available: 3000k/4000k/5000k
- All LED data and performance data is taken at an ambient temperature of +25°C

### Control Gear

Tridonic/OSRAM

- Standard LED
- DALI Dimming LED
- WI-FI

### Main Attributes

- Module efficacy up to 190 lm/W
- 50,000h L90 at 25°C
- Self Cooling
- Colour Rendering Index >80
- 7 Year Guarantee\*
- CE Marked

### Photometrics

-