




PRODUCT DETAILS



Dimensions



Accessories



LAMBDA LED SUSPENDED

LAMBDA LED SUSPENDED M LED
3550lm/840 1x26W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Suspended (SSD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Microprismatic diffuser (MCD)
BEAM ANGLE	70°/90°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG) External lead-in flexible cable
MATERIALS	Diffuser: PMMA Housing: sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
ACCESSORIES	Rope suspension RS-S 58
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	3550 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	26 W
SYSTEM EFFICACY	137 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L90 / B20
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS (L x W x H)	1260 x 120 x 60 mm
WEIGHT	4,6 kg


AREAS OF APPLICATION EDUCATION

HEALTH AND CARE

OFFICE



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.