



Product Service

CERTIFICATE

No. Z1A 021662 0299 Rev. 00

Factories: 021662

Model(s): COROCORD™
COR 1501, COR 1502, COR 1503, COR 1504,
COR 1505, COR 1506, COR 1507, COR 1508,
COR 1509, COR 1510, COR 1513, COR 1514,
COR 1515, COR 1515-1, COR 1516, COR 1517,
COR 1518, COR 1591, COR 1592

Parameter: Climbing course- elements clamed between steel posts.

Elements clamped with aluminium clamps consisting of 2 half-shells between steel posts with a centre distance of 6.00 m. Posts made of hot-dip galvanised tubular steel with a riveted rubber cap, rope thickness 19-21mm, ropes connected with stainless steel S clamps, spreader bars made of aluminium piping, membranes made of 7.5 mm thick polyester fabric, wood or plastic rungs, stands made of HDPE plastic.

COR 1501 Swaying bridge
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1502 Climbing ramp
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1503 Swaying seesaw
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.85 m

COR 1504 Tensegrity
L/W/H: 6.00/ 0.75/ 2.90 m
Max. falling height: 2.50 m

COR 1505 rope slalom
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1506 Crossed ladder
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1507 Rope screw
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

COR 1508 Flying carpet
L/W/H: 6.00/ 0.66/ 2.90 m
Max. falling height: 2.65 m

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

