

ITEM # RXM24WVJU9, FTXM-V SERIES

- Heat Pump outdoor unit using R-32 Refrigerant (may not be available in your area - check local codes regarding sale and installation).
- Available in 0.75, 1, 1.5 & 2 ton capacities
- Dependable heat pump operation from -13F in heating to 114F in cooling.
- 49.2 ft piping capabilities from factory refrigerant charge



[Specifications](#) | [Electrical Data](#) | [Refrigerant](#) | [Dimensions](#)

Specifications	
Rated Capacity (Min. - Max.) - Cooling	21600 (9000 - 26000) Btu/h
Rated Capacity (Min. - Max.) - Heating	24000 (9000 - 32200) Btu/h
Power Consumption Rated - Cooling	1728 W
Power Consumption Rated - Heating	1986 W
Power Factor - Cooling	97.3 - 97.3 %
Power Factor - Heating	99.0 - 99.0 %
SEER2 / HSPF2 - Cooling	22.00
SEER2 / HSPF2 - Heating	10.00
EER2 Rated	12.00 Btu/h-W
COP2 Rated	3.54 W/W
Amount of Additional Charge of Refrigerant	0.22 oz/ft 20 g/m

Casing Color	Ivory White
Compressor Type	Hermetically Sealed Swing Type
Compressor Model	2Y260BPBX1A
Airflow Rate (H) - Cooling	2179 ft ³ /min 61.7 m ³ /min
Airflow Rate (H) - Heating	2119 ft ³ /min 60.0 m ³ /min
Airflow Rate (SL) - Cooling	1833 ft ³ /min 51.9 m ³ /min
Airflow Rate (SL) - Heating	1833 ft ³ /min 51.9 m ³ /min
Fan Type	Propeller
Heat Exchanger Type	Waffle Fin
Heat Exchanger - Rows x Stages	2 x 32
Heat Exchanger - Fin per Inch	1.4
Sound Pressure Level (H) - Cooling	55 dBA
Sound Pressure Level (H) - Heating	56 dBA
Conditions Based on - Cooling	Indoor ; 80°FDB (26.7°CDB) / 67°FWB (19.4°CWB) Outdoor ; 95°FDB (35°CDB) / 75°FWB (24°CWB) Piping Length: 25 ft (7.5 m)
Conditions Based on - Heating	Indoor ; 70°FDB (21.1°CDB) / 60°FWB (15.6°CWB) Outdoor ; 47°FDB (8.3°CDB) / 43°FWB (6.1°CWB) Piping Length: 25 ft (7.5 m)
Drawing No.	3D133579
Notes	SL: The quiet fan level of the airflow rate setting.
Weight	132 lb 60 kg
Gross Weight	143 lb 65 kg

Voltage	208 to 230 V
Frequency	60 Hz
Number of Phases	1
Min. Circuit Ampacity	19.8 A
Max. Fuse Ampacity	20 A
Rated Load Amps	19.25 A
Outdoor Fan Motor - Rated Output	0.16 hp 123 W
Outdoor Fan Motor - Full Load Amps	0.58 A
Indoor Fan Motor - Rated Output	0.08 hp 61 W
Indoor Fan Motor - Full Load Amps	0.46 A

Refrigerant

Refrigerant Oil Type	FW68DA
Refrigerant Oil Charge	31.75 oz 0.9 L
Refrigerant Type	R-32
Refrigerant Charge	2.98 lb 1.35 kg

Dimensions

Depth	12 5/8 in 320 mm
Width	34-1/4 in 870 mm
Height	28-15/16 in 735 mm

Packaged Depth	18-1/4 in 464 mm
Packaged Width	41-1/2 in 1056 mm
Packaged Height	31-7/8 in 810 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	5/8 in 15.9 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Piping Length	98-1/2 in 30 m
Max. Interunit Height Difference	82-1/64 in 25 m
Chargeless	49.2 in 15 m

ITEM # FTXM24WVJU9, FTXM-V SERIES

- Wall Mounted unit using R-32 Refrigerant (may not be available in your area - check local codes regarding sale and installation).
- Built-in Wi-Fi to control the system with the Daikin Comfort Control App
- Hybrid Cooling technology controls humidity efficiently even in low cooling loads and maintains dehumidification effect after the target temperature is reached.
- CLEAN function dries the interior of the indoor unit to reduce the amount of condensation present.
- The indoor unit has been re-

[+ more](#)



[Specifications](#) | [Electrical Data](#) | [Dimensions](#)

Specifications	
Rated Capacity (Min. - Max.) - Cooling	21600 (9000 - 26000) Btu/h
Rated Capacity (Min. - Max.) - Heating	24000 (9000 - 32200) Btu/h
Power Consumption Rated - Cooling	1728 W
Power Consumption Rated - Heating	1986 W
Power Factor - Cooling	97.3 - 97.3 %
Power Factor - Heating	99.0 - 99.0 %
SEER2 / HSPF2 - Cooling	22.00
SEER2 / HSPF2 - Heating	10.00
EER2 Rated	12.00 Btu/h-W
COP2 Rated	3.54 W/W

Amount of Additional Charge of Refrigerant	0.22 oz/ft 20 g/m
Front Panel Color	White (N-9.5)
Airflow Rate (H) - Cooling	844 ft ³ /min 23.9 m ³ /min
Airflow Rate (H) - Heating	844 ft ³ /min 23.9 m ³ /min
Airflow Rate (M) - Cooling	653 ft ³ /min 18.5 m ³ /min
Airflow Rate (M) - Heating	607 ft ³ /min 17.2 m ³ /min
Airflow Rate (L) - Cooling	498 ft ³ /min 14.1 m ³ /min
Airflow Rate (L) - Heating	498 ft ³ /min 14.1 m ³ /min
Airflow Rate (SL) - Cooling	452 ft ³ /min 12.8 m ³ /min
Airflow Rate (SL) - Heating	452 ft ³ /min 12.8 m ³ /min
Fan Type	Cross Flow Fan
Fan Speed	5 Steps, Quiet, Auto
Heat Exchanger Type	Multi Slit Fin
Heat Exchanger - Rows x Stages	1 × 4 1 × 8 2 × 18
Heat Exchanger - Fin per Inch	18
Sound Pressure Level (H) - Cooling	51 dBA
Sound Pressure Level (H) - Heating	51 dBA
Sound Pressure Level (M) - Cooling	44 dBA
Sound Pressure Level (M) - Heating	42 dBA
Sound Pressure Level (L) - Cooling	37 dBA

Sound Pressure Level (L) - Heating	37 dBA
------------------------------------	--------

Sound Pressure Level (SL) - Cooling	34 dBA
-------------------------------------	--------

Sound Pressure Level (SL) - Heating	34 dBA
-------------------------------------	--------

Weight	33 lb 15 kg
--------	----------------

Gross Weight	46 lb 21 kg
--------------	----------------

Electrical Data

Voltage	208 to 230 V
---------	--------------

Frequency	60 Hz
-----------	-------

Number of Phases	1
------------------	---

Min. Circuit Ampacity	19.8 A
-----------------------	--------

Max. Fuse Ampacity	20 A
--------------------	------

Rated Load Amps	19.25 A
-----------------	---------

Outdoor Fan Motor - Rated Output	0.16 hp 123 W
----------------------------------	------------------

Outdoor Fan Motor - Full Load Amps	0.58 A
------------------------------------	--------

Indoor Fan Motor - Rated Output	0.08 hp 61 W
---------------------------------	-----------------

Indoor Fan Motor - Full Load Amps	0.46 A
-----------------------------------	--------

Dimensions

Depth	10-13/16 in 275 mm
-------	-----------------------

Width	43-5/16 in 1100 mm
-------	-----------------------

Height	11-3/4 in 299 mm
--------	---------------------

Packaged Depth	15-1/2 in 393 mm
Packaged Width	47-11/16 in 1212 mm
Packaged Height	15-13/16 in 401 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	5/8 in 15.9 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Piping Length	98-1/2 in 30 m
Max. Interunit Height Difference	82-1/64 in 25 m
Chargeless	49.2 in 15 m