

Job Name:

Location:

Engineer:

Submitted to:

Submitted by:

Reference:

Date:

Approval:

Construction:



Unit #:

Drawing #:

## KEY FEATURES:


- Can be installed up to 2' from the ceiling
- Invert technology
- Refrigerant Sensor
- Humidity Sensor
- Auto-Swing for vertical and horizontal louvers
- Easy to remove blower wheel, magnetic filter on top
- Larger air inlet/outlet air flow
- Compatible with regular (-13°F) or Hyper (-22°F) outdoor units


NOTES:



| Indoor Model                                |                    |           | CH-PRO33HASTWM-230VI                          |
|---------------------------------------------|--------------------|-----------|-----------------------------------------------|
| Power supply                                |                    | V, Ph, Hz | 208-230V, 1Ph, 60Hz                           |
| Communication wiring                        |                    |           | AWG 14-4                                      |
| Cooling                                     | Capacity           | Btu/h     | 33,000 (15,000~37,000)                        |
|                                             | Input              | W         | 2,750 (440~3,450)                             |
|                                             | Rated current      | A         | 12.7 (3.1~15.4)                               |
|                                             | EER/EER2           | Btu/w     | 12.0                                          |
|                                             | SEER/SEER2         | Btu/w     | 19.5                                          |
| Heating at 47 °F                            | Capacity           | Btu/h     | 36,000 (19,700~37,800)                        |
|                                             | Input              | W         | 3,131 (1,250~3,970)                           |
|                                             | Rated current      | A         | 13.7 (6.8~17.5)                               |
|                                             | COP                | W/W       | 3.37                                          |
|                                             | HSPF4/HSPF2-4      |           | 10.5                                          |
|                                             | HSPF5/HSPF2-5      |           | 8.6                                           |
| Indoor fan motor                            |                    | Qty       | 1                                             |
|                                             |                    | Input (W) | 58                                            |
|                                             |                    | RLA (A)   | 1.6                                           |
| Indoor air flow (Turbo/Hi/Med/Lo) (No duct) |                    | CFM       | 865.2 / 735.8 / 600.4 / 423.8                 |
| ESP (range)                                 |                    | In.wg.    |                                               |
| Indoor noise level (Hi/Med/Lo)              |                    | dB(A)     | 53/46.5/35.5                                  |
| Dehumidification                            |                    | Pnt/H     | 8.88                                          |
| Indoor unit                                 | Dimensions (WxDxH) | inch      | 47.13 x 11.02 x 14.61                         |
|                                             | Packing (WxDxH)    | inch      | 50.39x14.17x17.91                             |
|                                             | Net/Gross weight   | lbs       | 43.21/55.78                                   |
| Drainage water pipe diameter                |                    | inch      | 5/8"                                          |
| Refrigerant piping (Liquid side/Gas side)   |                    | inch      | 3/8"/3/4"                                     |
| Design pressure                             |                    | PSIG      | 550/340                                       |
| Controller                                  |                    |           | wire controller + remote controller available |
| Room temperature                            | Cooling            | F         | 60~90                                         |
|                                             | Heating            | F         | 32~86                                         |

| Outdoor Model                              |                          |           | CH-RHP33-230VO        |
|--------------------------------------------|--------------------------|-----------|-----------------------|
| Power supply                               |                          | V, Ph, Hz | 208-230V, 1Ph, 60Hz   |
| Min. circuit ampacity                      |                          | A         | 34                    |
| Max. fuse                                  |                          | A         | 35                    |
| Compressor                                 | Model                    |           | KTF420D62UNT          |
|                                            | Type                     |           | Twin-ROTARY           |
|                                            | Brand                    |           | GMCC                  |
|                                            | Capacity                 | Btu/h     | 45,890 ± 3%           |
|                                            | Input                    | W         | 3,540 ± 3%            |
|                                            | Rated current (RLA)      | A         | 24.5                  |
|                                            | Refrigerant oil          | oz        | VG74 33.8             |
| Outdoor fan motor                          | Qty                      |           | 1                     |
|                                            | Input                    | W         | 230                   |
|                                            | RLA                      | A         | 1.5                   |
|                                            | Speed                    | r/min     | 800/700/500           |
| Outdoor air flow (Max)                     |                          | CFM       | 2,235.3               |
| Outdoor noise level (Max)                  |                          | dB(A)     | 63.5                  |
| Throttle type                              |                          |           | EXV                   |
| Outdoor unit                               | Dimensions (WxDxH)       | inch      | 37.24 x 16.14 x 31.89 |
|                                            | Packing (WxDxH)          | inch      | 42.91 x 19.68 x 34.84 |
|                                            | Net/Gross weight         | inch      | 156.97/167.99         |
| Refrigerant                                | Type                     |           | R454B                 |
|                                            | Precharge                | ft        | 25                    |
| Additional charge for 1/4 inch liquid pipe |                          | oz        | /                     |
| Additional charge for 3/8 inch liquid pipe |                          | oz        | 0.32                  |
| Refrigerant piping                         | Liquid side/Gas side     | inch      | 3/8"/3/4"             |
|                                            | Max. pipe length         | ft        | 164                   |
|                                            | Max. difference in level | ft        | 82                    |
| Ambient temperature                        | Cooling                  | F         | -22 ~ 122             |
|                                            | Heating                  | F         | -22~75                |





| Capacity | Body Code | Unit | W      | D     | H      |
|----------|-----------|------|--------|-------|--------|
| 6k~12k   | B         | mm   | 857    | 231   | 300    |
|          |           | inch | 33-3/4 | 9-1/8 | 11-3/4 |
| 18k      | C         | mm   | 1024   | 246   | 321    |
|          |           | inch | 40-1/4 | 9-3/4 | 12-5/8 |
| 24k~36k  | D         | mm   | 1197   | 280   | 371    |
|          |           | inch | 47-1/8 | 11    | 14-5/8 |