

Outdoor Unit Heat Pump Ductless System

Outdoor Model: D5CSRAH36AAK


Job Data:

Location:

Tag #:

Carrier#:


Date:



- OUTDOOR STANDARD FEATURES**
- Variable Speed (Inverter)
 - Factory installed Base Pan Heater
 - Factory installed Crankcase Heater
 - Low Voltage Controls
 - Auto-Restart function
 - Condenser High Temp Protection
 - Quiet operation
 - Anti-corrosive fin coating

- LIMITED WARRANTY***
- Seven (7) years compressor and five (5) years parts warranty.

NOTE: Images for illustration purposes only. Actual models may be slightly different.



OUTDOOR UNIT DIMENSIONS						
Capacity	Unit	W	D	H	L1	L2
9K/12K	mm	765	303	555	452.4	313.82
	inch	30.12	11.93	21.85	17.81	12.36
18K	mm	890	342	673	663	379.59
	inch	35.04	13.46	26.5	26.1	14.94
24K ~ 36K	mm	946	410	810	672.96	454.8
	inch	37.24	16.14	31.89	26.49	17.19

Outdoor - Heat Pump			
System	Outdoor Model #		D5CSRAH36AAK
	Outdoor Size		36000
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208-230/1/60
	MCA	A.	33
	MOA	A.	35
	SCCR	kA	5
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	-13~122(-25~50)
	Heating Outdoor DB Min - Max	°F(°C)	-13~75(-25~24)
Piping	Min. Piping Length	ft (m)	9.8 (3)
	Standard Piping Length	ft. (m)	24.6 (7.5)
	Total Piping Length	ft (m)	213.25(65)
	Piping Lift	ft (m)	98.43(30)
	Pipe Connection Size - Liquid	in (mm)	3/8in(9.52mm)
	Pipe Connection Size - Suction	in (mm)	5/8in(15.9mm)
Refrigerant	Refrigerant Type		R454B
	Charge	lbs (kg)	7.05(3.2)
	Add'l Refrigerant (between Std & Max Piping Lengths)	Oz/ft (g/m)	0.32(30)
Outdoor Coil	Face Area	Sq. Ft.	8.14
	No. Rows		3
	Fins per inch		19
	Circuits		6
Compressor	Type		ROTARY
	Model		KTF250D22UMT
	Oil Type		ESTER OIL
	Oil Charge	Fl. Oz.	22.66
Airflow & Sound	Rated Current	RLA	10
	Airflow	CFM	2237.9
Dimensions	Sound Pressure	dB(A)	63
	Height	in (mm)	31.89(810)
	Width	in (mm)	37.24(946)
	Depth	in (mm)	16.14(410)
	Net Weight	lbs (kg)	150.36(68.2)
	Shipping Height	in (mm)	34.84(885)
	Shipping Width	in (mm)	42.91(1090)
	Shipping Depth	in (mm)	19.68(500)
	Shipping Net Weight	lbs (kg)	160.28(72.7)

* Condensing unit above or below indoor unit



R-454B