

High Wall Heat Pump Ductless System

Indoor Model: D5FPHAH18XAK

Job Data:

Tag #:

Date:

Location:


Carrier#:



- INDOOR STANDARD FEATURES**
- Modes: Cool, Heat, Dry, Fan, Auto
 - Four fan speeds
 - Sleep Mode
 - Turbo Mode
 - Follow Me (senses temperature at handheld remote)
 - Auto-Restart function
 - Quiet indoor operation
 - Anti-corrosive fin coating
 - Factory Pre- installed Leak Detection System
 - Pipe Connection Size - Liquid: 3/8in (9.52mm)
 - Pipe Connection Size - Suction: 5/8in (15.9mm)

- LIMITED WARRANTY***
- Seven (7) years compressor and five (5) years parts warranty.

NOTE: Images for illustration purposes only. Actual models may be slightly different.



INDOOR UNIT DIMENSIONS				
Capacity	Unit	W	D	H
18K	mm	1140	275	370
	inch	44.88	10.83	14.57

D5FPHAH18XAK			
System	Indoor Model #		D5FPHAH18XAK
	Indoor Size		18000
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208-230V/1/60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	3
Operating Range	Cooling Indoor DB Min - Max	*F(*C)	60~90(16~32)
	Heating Indoor DB Min - Max	*F(*C)	32~86(0~30)
Indoor Coil	Face Area	Sq. Ft.	3.6
	No. Rows		3
	Fins per inch		20
	Circuits		7
Indoor Unit	Number of Fan Speeds		1000/850/630
	Airflow (highest to lowest)	CFM	812.3 / 618.0 / 412.0 / 317.8 / N/A
	Sound Pressure (highest to lowest)	dB(A)	N/A/43.5/38.5/27/16
	Moisture Removal	L/h	1.1
	Air Throw Data	ft(m)	30.1(9.18)
Dimensions	Height	in (mm)	14.57(370)
	Width	in (mm)	44.88(1140)
	Depth	in (mm)	10.83(275)
	Net Weight	lbs (kg)	43.65(19.8)
	Shipping Height	in (mm)	13.98(355)
	Shipping Width	in (mm)	48.43(1230)
	Shipping Depth	in (mm)	17.91(455)
	Shipping Net Weight	lbs (kg)	55.56(25.2)
CONTROLS			
Standard	Wireless Remote Controller (*F/*C Convertible)		
	Wi-Fi™ Kit High Wall		KSAlF0701AAA
Optional	Wired Remote Control 7 Day Programmable		KSACN1401AAA
	Wired Remote Control with Timer Function		KSACN1201AAA
	24V Mini Interface		KSAlC0601230



R-454B